



## Access Control Terminal

DS-K1T502DBWX-C

SKU: 131181    UPC: 842571000000

HIKVISION DS-K1T502DBWX-C ALL-IN-ONE ACCESS CONTROL TERMINAL IP65 AND IK09 PROTECTION TWO WAY AUDIO

### Features

Manage access control, video intercoms, and video security with one device  
IP65 & IK09 protections, as well as increased stability with zinc alloy materials  
Multiple authentication methods, including card, etc.  
Remote control via the Hik-Connect mobile app  
Connects to external access controller via Wiegand protocol  
Two-way audio via SIP 2.0 protocol  
RS-485 communication for connecting external card reader  
Available models:  
DS-K1T502DBWX-C

Specifications System Operating System Linux Video Lens 1 Resolution 2 MP FOV HFOV = 110°; VFOV = 81°; DFOV = 122° Video Standard PAL (Default) and NTSC Network Wired Network 10 M/100 M self-adaptive Wi-Fi Support Bluetooth Support Interface Network Interface 1 Lock Control 1 Exit Button 1 Door Contact Input 1 Alarm Input 1 Alarm Output 1 TAMPER 1 RS-485 1 Wiegand 1 (Output only) SD Card Slot 1 Capacity Card Capacity 100,000 Event Capacity 300,000 Authentication Card Type Mifare 1 card; DESfire card Card Reading Distance 0 ~ 3 cm Function Two-Way Audio Support Hik-Connect Support General Power Supply 1 A ¼ DC 12 V ~ DC 24 V Power Consumption 12 W Working Temperature -40 °C ~ +70 °C (-40 °F ~ +158 °F) Protective Level IK09, IP65 Language Arabic, English, French, Indonesian, Italian, Portuguese (Brazil), Russian, Spanish (Europe), Thai, Ukrainian, Vietnamese