



Square Grille for In-Ceiling Speaker

CS160S

SKU: 62687

Monitor Audio In-Ceiling Speaker CS160

The CS160 in-ceiling model couples a 6-inch MMP II driver with a pivoting C-CAM Gold Dome tweeter. Delivering great imaging and dynamics from a brilliantly compact design, the CS160 is perfect for high-performance, ultra-discreet custom-installed systems.

Please specify a round or square grille option when ordering.

Features

- slim mounting depth allows for installation in the ceiling or wall where space is at a premium
- ideal for an in-ceiling or in-wall music system or overhead surround effects channel of a home theater system
- pivoting 1" gold dome C-CAM® (Ceramic-Coated Aluminum/Magnesium) tweeter for detailed sound and extended high-frequency response
- 6" MMP® II (Metal Matrix Polymer) woofer
- recommended amplifier power: 15-70 watts
- frequency response: 60-30,000 Hz
- sensitivity: 88 dB
- impedance: 6 ohms
- patented Tri-Grip® mounting system ensures maximum surface seal for better bass and midrange clarity
- paintable removable square magnetic grille
- cutout diameter: 6-11/16"
- overall dimensions with square grille: 7-13/16"W x 7-13/16"H
- mounting depth: 3-7/8"
- weight: 4.6 lbs.

Frequency Response 60 Hz - 30 kHz Nominal Impedance 6 ohms Sensitivity (1W@1M) 88 dB Maximum SPL 2 dB A Power Handling (RMS) 70 W Recommended Amplifier Requirements 15 - 70 W Drive Unit Complement 1 x 6" MMP II cone bass driver. 1 x 1" (25 mm) C-CAM pivoting Gold Dome tweeter Acoustic Configuration 2-way Overall Dimensions (Including Grille (H x W)) Round: 204.2 mm (8 1/16") Square: 199.2 x 199.2 mm (7 13/16 x 7 13/16") Mounting Depth 99 mm (3 7/8") Cut-Out Hole Diameter 170 mm (6 11/16") Fixing Type 3 position Tri-Grip dog fixings Connection Gold plated "push"™ type terminals Grille Attachment Magnetic Construction Material Mineral filled ABS, RoHS compliant Weight 10 kg (4 lb 10 oz) Pre-Construction Bracket CB5 Pre-Construction Bracket (Blue) Back Box CCBOX-R | CMBOX-R