



## 4MP IP Turret Camera

O4T7

SKU: 118014

### Product Descriptions:

Speco 4MP H.265 AI IP Turret Camera IR 2.8MM lens included junction box white housing

### Features

- Supports up to 4MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 98<sup>TM</sup> (depending on scene reflection)
- Micro SD slot up to 128GB (card not included)
- True WDR (wide dynamic range) operation
- IP67 compliant, weather-resistant
- Junction box included (works with NPT/BSP specifications)
- Conformant with ONVIF Profile T
- 5-year warranty

Specifications: Sensor 4 MP 1/3" CMOS Focal Length 2.8mm Lens Field of View Horizontal: 100.4° IR Cut Filter Mechanical Day/Night True Minimum Illumination Color: 0.005 Lux B&W: 0 Lux Shutter Speed 1/100,000 to 1/30 Seconds Video Streaming Resolution 2592 x 1520 at 30 fps (8 Mb/s ) Supported Video Compression H.264, H.265, MJPEG Multi-View Streaming Yes, 3 Streams Automatic Gain Control Yes Audio 1- or 2-Way Audio One-Way Audio Formats G.711 Built-In Mic Yes External Audio Input 3.5 mm Networking Security Digest Authentication, HTTPS, IEEE 802.1X, IP Address Filtering, MAC Address Filtering, Password Protection, Watermark Supported Protocols DDNS, DHCP, FTP, HTTP, IPv4/v6, NTP, PPPoE, RTSP, SMTP, SNMP v1/v2c/v3 (MIB-II), UDP, UPnP System Integration Application Programming Interface (API) ONVIF Profile T Analytics Motion, Missing Object, Abandoned Object, Intrusion, Vehicle, Human, Tampering, Scene Change & Face Detection Event Trigger Yes Event Action Recording, Notification, Alarm Data Streaming Yes System Requirements Mobile Operating Systems iOS, Android Environmental Operating Temperature -40 to 140°F / -40 to 60°C Operating Humidity 0 to 95% IP Rating IP67 General Media/Memory Card Slot Single Slot: microSD/microSDHC/microSDXC [128 GB Maximum] Pan/Tilt None I/O Connections 1 x RJ45 1 x Power IR Range 98' / 29.9 m Video Management Software SecureGuard VMS & CMS for PC Applications SecureGuard Client & Speco Blue for iOS & Android Internal Storage None External Storage Options Cloud Power Source DC, PoE 802.3af (15 W) Power Consumption 7.5 W Dimensions Å, : 3.7 x H: 3.3" / Å, : 94.0 x H: 83.8 mm Weight 1 lb / 454 g Packaging Info Package Weight 2.34 lb Box Dimensions (LxWxH) 6.7 x 6.3 x 6.2"