



2MP ColorVu Audio Fixed Mini Bullet Camera with 2.8mm Lens

DS-2CE10DF3T-FS 2.8mm

SKU: 118724 UPC: 842571000000

Hikvision 2MP ColorVu Audio Fixed Mini Bullet Camera DS-2CE10DF3T-FS 2.8mm

Features

- High-quality imaging with 2 MP, 1920 - 1080 resolution
- 24/7 color imaging with F1.0 aperture
- Clear imaging against strong backlight due to 130 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- 2.8 mm fixed focal lens
- Up to 20 m white light distance for bright night imaging
- High-quality audio with audio over coaxial cable, built-in mic
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)

Specifications Camera Image Sensor 2 MP CMOS Resolution 1920 (H) x 1080 (V) Illumination 0005 Lux @ (F1.0, AGC ON), 0 Lux with white light Shutter Time PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s Day & Night 24/7 Color Imaging Angle Adjustment Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360° Signal System PAL/NTSC Slow Shutter 16 times Light Alarm Solid Light Alarm (White Light) Lens Lens Type 8 mm, 3.6 mm fixed focal lens Focal Length & FOV 8 mm, horizontal FOV: 98°, vertical FOV: 52°, diagonal FOV: 116° 6 mm, horizontal FOV: 77°, vertical FOV: 42°, diagonal FOV: 91° Lens Mount M12 Illuminator Supplement Light Range Up to 20 m Smart Supplement Light Yes Supplement Light Type White Light Image Image Parameters Switch STD/HIGH-SAT/HIGHLIGHT Image Settings Brightness, Contrast, Mirror, Defective Pixel Correction, Sharpness, Anti-Banding, AGC Frame Rate TVI: 1080p @ 25 fps/30 fps CVI: 1080p @ 25 fps/30 fps AHD: 1080p @ 25 fps/30 fps CVBS: PAL/NTSC Day/Night Mode Color Wide Dynamic Range (WDR) 130 dB Image Enhancement WDR, BLC, HLC, Global, HLS Privacy Mask 4 programmable privacy masks Noise Reduction 3D DNR/2D DNR White Balance Auto/Manual Interface Video Output Switchable TVI/AHD/CVI/CVBS Built-In Microphone Yes Event Motion Detection 4 programmable motion areas General Material Metal Dimension 1 mm x 70 mm x 70 mm (6.34" x 2.76" x 2.76") 388 g (0.86 lb.) Operating Condition -40°C to 60°C (-40°F to 140°F), Humidity: 90% or less (non-condensing) Communication HIKVISION-C Language English Power 12 VDC ± 25%, Max. 4.2 W *You are recommended to use one power adapter to supply the power for one camera.

Approval Protection IP67