



## 16-Channel 5MP 2U H.265 AcuSense DVR

iDS-9016HUHI-M8/S

SKU: 131060    UPC: 842571000000

Hikvision 16-ch 5MP 2U H.265 AcuSense DVR iDS-9016HUHI-M8/S

### Features

- Up to 16-ch analog camera inputs and 8 SATA interfaces
- H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression
- Up to 8 MP@8 fps/5 MP@12 fps encoding capability
- HDTV/AVI/CVI/CVBS/IP video inputs
- Up to 34-ch network camera inputs
- POS triggered recording and POS information overlay
- RAID 0, 1, 5, 6, 10 for even more reliable data storage, effectively avoids data loss risks

**Specifications**

**Recording** Video compression: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 Encoding Resolution: 8 MP/3K/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF Frame Rate Main stream: 8 MP@8 fps/3K@12 fps/5 MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream: WD1/4CIF/CIF@25 fps (P)/30 fps (N) Video Bitrate: 32 Kbps to 10 Mbps Dual-Stream Support Stream Type: Video, Video & Audio Audio Compression: G.711u Audio Bitrate: 64 Kbps Video And Audio IP Video Input: 18-ch (up to 34-ch) Up to 12 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras Analog Video Input: 16-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection HDTV Input: 8 MP, 3K, 5 MP, 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60 AHD Input: 5 MP, 4 MP, 720p25, 720p30, 1080p25, 1080p30 HDCVI Input: 4 MP, 720p25, 720p30, 1080p25, 1080p30 CVBS Input: PAL/NTSC CVBS Output: 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 x 576, NTSC: 704 x 480 Video Loop Support HDMI 1 Output: 1-ch, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz HDMI 2 Output: 1-ch, 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60Hz, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz VGA Output: 1-ch, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz Video Output Mode: HDMI1/VGA simultaneous output, HDMI2/VGA independent output Audio Input: 16-ch, RCA (2.0 Vp-p, 1 KΩ) Audio Output: 2-ch, RCA (Linear, 1 KΩ) Two-Way Audio: 1-ch, RCA (2.0 Vp-p, 1 KΩ) (independent) Synchronous Playback: 16-ch Network Total Bandwidth: 320 Mbps Network Protocol: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF, SNMP Remote Connection: 128 Network Interface: 2, RJ45 10M/100M/1000M self-adaptive Ethernet interface Auxiliary Interface: SATA8 SATA interfaces ESATA Support Capacity: Up to 12 TB capacity for each disk Serial Interface: RS-232, RS-485 (full-duplex), keyboard Alarm In/Out: 16/8 USB Interface Front panel: 2 x USB 2.0 Rear panel: 1 x USB 3.0 General Power Supply: 100 to 240 VAC, 50 to 60 Hz Consumption: 35 W (without HDD) Working Temperature: -10 °C to +55 °C (+14 °F to +131 °F) Working Humidity: 10% to 90% Dimension (W x D x H): 445 x 465 x 88 mm (17.5 x 18.3 x 3.5 inch) Weight: 9 kg (without HDD, 19.8 lb.)

\*Product performance is based on testing in a controlled environment. Your results may vary due to several external and