



VGA IP Mini Dome Camera

DS-2CD7133-E

SKU: 16723

Hikvision VGA IP Mini Dome Camera DS-2CD7133-E

Features

- 1/4 progressive scan CMOS
- H.264 / MPEG4 / MJPEG video compression
- Super low illumination
- Day / night auto switch
- PoE
- IP66 rating
- 3-axis adjustment

Camera Image sensor 1/4" progressive scan CMOS Min. illumination 0.01 lux@F1.2, AGC on, 0.02 lux@F1.8, AGC on
Shutter time 1/25s ~ 1/100,000s Lens 4 mm @F1.8 (2.8, 6, 8mm optional), angle of view: 52° Lens mount M12 Angle
adjustment Pan: ± 15°, tilt: 0 ~ 90°, rotation: ± 15° Day & night Electronic Compression Standard Video compression
H.264 / MPEG4 / MJPEG Bit rate 32 Kbps ~ 8 Mbps Dual stream Yes Image Max. image resolution 640 x 480 Frame
rate 50 Hz: 25 fps (640 x 480) 60 Hz: 30 fps (640 x 480) Image settings Saturation, brightness, contrast adjustable
through client software or web browser Network Network storage NAS (iSCSI optional) Alarm trigger Motion detection,
tampering alarm, network disconnect, IP address conflict Protocols TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP,
PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional) Security Password protection,
watermark System compatibility ONVIF, PSIA, CGI Interface Communication interface 1 RJ45 10M / 100M ethernet port
Reset button Yes General Operating conditions -10°C ~ 60°C (14°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply 12 VDC ± 10%, PoE (802.3af) Power consumption max. 4W Impact protection IEC60068-275Eh, 50J;
EN50102, up to IK10 Weather-proof rating IP66 Dimensions 99.9 x 97.5 x 46.5 mm (3.93" x 3.84" x 1.83") Weight 250g
(0.55 lbs)