



5MP Fixed Turret Camera with 2.8mm

DS-2CE56HOT-IT3F 2.8mm

SKU: 25195 UPC: 842571000000

The Hikvision DS-2CE56HOT-IT3F 5 MP Outdoor Turret Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video. EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 130 feet (40 meters). The 2.8 mm, 3.6 mm, 6 mm, 8 mm, and 12 mm fixed lens options are optimized for viewing angles that fit any situation. DWDR (Digital Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

Features

- 5 MP High Performance CMOS
- Up to 2560 x 1944 Resolution
- 2.8 mm, 3.6 mm, 6 mm, 8 mm, and 12 mm Fixed Lens Options
- 3D DNR, DWDR
- EXIR 2.0 with up to 130 ft (40 m) IR Range
- Multiprotocol Output: TVI/AHD/CVI/CVBS
- Up-the-Coax (HIKVISION-C)
- IP67 Protection

Camera Image Sensor 5 MP progressive scan CMOS Resolution 2560 (H) x 1944 (V) Minimum Illumination Color: 0.01 Lux @ (Æ'1.2, AGC on), 0 Lux with IR Shutter Speed 1/30 s to 1/50, 000 s Lens 2.8 mm, 3.6 mm, 6 mm, 8 mm, and 12 mm fixed lens options Horizontal Field of View 85.5° (2.8 mm), 80.1° (3.6 mm), 57.1° (6 mm), 41° (8 mm), 25.7° (12 mm) Lens Mount M12 Day / Night IR cut filter Angle Adjustment Pan: 0° to 360°; tilt: 0° to 75°; rotate: 0° to 360° Synchronization Internal synchronization Frame Rate 5 MP @ 20 fps, 4 MP @ 30 fps, 1080p @ 30 fps Menu AGC Supported Day/Night Mode Auto/color/BW (black and white) White Balance ATW/MWB BLC Supported DWDR Supported Language English Functions Brightness, Sharpness, DNR, Mirror, Smart IR Interface TVI Video Output 1 HD analog output Switch Button TVI/AHD/CVI/CVBS General Operating Conditions -40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation) Power Supply 12 VDC ± 25% Power Consumption Maximum 4.3 W Protection Level IP67 Material Enclosure: plastic; main body: metal IR Range Up to 130 ft (40 m) Communication Up-the-Coax, Protocol: HIKVISION-C (HD-TVI output) Dimensions Å~ 4.33" x 3.67" (Å~ 110 mm x 93.2 mm) Weight Approximately 0.77 lbs (350 g)