



5MP HD EXIR Outdoor Turret Camera with 3.6mm

DS-2CE56H1T-ITM 3.6mm

SKU: 16377 UPC: 842571000000

The ivory DS-2CE56H1T-ITM 5MP Outdoor HD-TVI Turret Camera with Night Vision & 3.6mm Lens from Hikvision is equipped with a 1/3" progressive scan CMOS sensor to capture 2592 x 1944 resolution video at up to 20 fps. Built-in EXIR technology delivers up to 65' of night vision. The 3.6mm fixed lens features a 70.1° horizontal field of view. HD-TVI technology allows the camera to transmit HD video over coaxial cables. This device is housed in an IP67-rated enclosure that is suitable for outdoor use.

Features

- 2592 x 1944 at 20 fps
- Up to 65' of Night Vision
- 3.6mm Fixed Lens
- 70.1° Horizontal Field of View
- UTC (Up-the-Coax) Connection
- IP67 Rated for Outdoor Use

Camera Image Sensor 5 MP CMOS image sensor Effective Pixels 2560 (H) x 1944 (V) Min. illumination Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR Shutter Time PAL: 1/25 s to 1/50, 000 s, NTSC: 1/30 s to 1/50, 000 s Lens 2.8 mm, 3.6 mm, 6 mm fixed focal Lens Horizontal Field of View 89°(2.8 mm), 68.4°(3.6 mm), 46°(6 mm) Lens Mount M12 Day & Night IR cut filter Angle Adjustment Pan: 0°to 360°; Tilt:0°to 75°; Rotate: 0°to 360° Synchronization Internal synchronization Frame Rate 2560 x 1944@20fps, 2560 x 1944@12.5fps 2560 x 1440@30fps, 2560 x 1440@25fps (default) 1920 x 1080@30fps, 1920 x 1080@25fps Menu AGC Support D/N Mode Auto/Color/BW (Black and White) White Balance ATW/MWB BLC Support DWDR (Digital Wide Dynamic Range) Support Language English, Chinese Functions Brightness, Sharpness, DNR, Mirror, Smart IR Interface Video Output 1 HD analog output General Operating Conditions -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) Power Supply 12 VDC ±25% Power Consumption Max. 5 W Protection Level IP67 Material Metal IR Range Up to 20 m Communication Up the coax, Protocol: HIKVISION-C (TVI output) Dimensions 91 mm x 82.6 mm x 68.3 mm (3.58" x 3.25" x 2.69") Weight Approx. 350 g (0.77 lb)