

Integra.

6-Disc CD Changer

CDC-3.4

SKU: 152320 UPC: 751398000000



Your Never-Ending Playlist

The newly redesigned Integra CDC-3.4 six-disc CD changer delivers an unparalleled listening experience. It features smooth & quiet mechanical operation, plus a soft blue light that illuminates the disc tray for better visibility. You can also load up to 5 discs while one is still playing for extended listening times without interruption.

Features

- Change up to 5 discs without stopping playback
- Multi-bit digital to analog converter
- Vector linear shaping circuitry (VLSC) for a noise-free signal path
- Cross-Interleaved Reed-Solomon Code (CIRC) Error Correction
- 128-times oversampling
- Anti-Resonant Aluminum Front Panel
- Illuminated Disc Tray
- 2 Digital Outputs (1 Optical, 1 Coaxial)
- Analog Audio Output
- Parallel Audio Outputs- All Outputs Simultaneously Active
- High-Quality Gold-Plated Terminals for Superior Signal Transmission
- CD-R/RW with MP3 Playback Support
- 6 Repeat Modes: Entire Disc, All Discs, Random Tracks, Memory Tracks, Random Memory, Single Folder, Single Track
- Shuffle / True Random Play (Including MP3)
- Direct Track Access
- 40-Track Memory Playback
- Bi-directional RS-232 Control Port
- Rear Panel IR Input and Output
- 9 Unique IR Codes Sets for Stacking Multiple Units
- RI (Remote Interactive) Input and Output
- Optional Rack Mount Kit Available (IRK-180-4C)

- Error Correction System: Cross-Interleave
- Reed-Solomon Code (CIRC)
- Multi-Bit D/A Converter
- Digital Filter: 128 Times Oversampling
- Frequency Response: 5 Hz – 20 kHz
- Harmonic Distortion: 0.005% (at 1 kHz)
- Dynamic Range: 96 dB
- Signal-to-Noise Ratio: 98 dB
- Channel Separation: 92 dB (at 1 kHz)
- Wow and Flutter: Below Threshold of Measurability
- Optical: -22.5dBm Optical Connector
- Coaxial: 0.5 V(p-p), 75 Ω , RCAx 1
- Analog: 2.0 V RMS, 470 Ω , RCAx 1

The KOA logo, featuring the letters 'KOA' in a bold, red, sans-serif font.

- Power Supply: AC 120 V, 60 Hz
- Power Consumption: 10 W
- Dimensions (W x H x D): 17-1/8" x 5-3/16" x 17-3/16" (435 x 131 x 436 mm)
- Weight: 15.2 lbs. (6.9 kg)
- Optional Mounting Kit: IRK-155-3D
- U Dimension: 4U
- Carton
- Dimensions (W x H x D): 21-1/4" x 9-3/4" x 21" (641 x 248 x 533 mm)
- Weight: 19 lbs. (8.6 kg)