



D1101KH Modern Flush-Mount IP Video Intercom - Stainless Steel

423867598

SKU: 65360 UPC: 4260423867598

DoorBird D1101KH Intercom system for single-family homes and businesses with 1 unit, 1 call button

Features

- Video intercom including flush-mounting housing
- LAN connection (PoE compatible)
- 2-way audio
- Ultra-wide angle lens, 1080p, night vision, IR LEDs
- 4D motion sensor
- Keypad
- Intercom with 1 freely configurable bistable switching relay

Front Panel	3 mm (0.12 in) For further materials and colours see material board and Online Shop.
Mounting Housing (backbox)	Stainless steel
Mounting Type	Flush-mounted, surface-mounted version sold separately
Call Button	Plastic Metal cover plate and engraving available separately
Nameplate	Illuminated
Keypad Module	12 keys, illuminated, configurable via App, e.g. <ul style="list-style-type: none"> • Individual PIN codes • Individual events (e.g. switch a relay, HTTP(s) request) • Individual schedules • Up to 1000 PIN codes manageable
Power supply	15 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)
Weight	1600 g

Connectors	<ul style="list-style-type: none"> • LAN/PoE (T+, T-, R+, R-) • Bistable latching relay, max. 1-24 V DC/AC, 1 A, e.g. for electric door opener • External input for external door opener button • 15 V DC input (+, -), max. 15 W
Protection Class	IP65, IK08
Approvals	IP65, CE, FCC, IC, RoHS, REACH, IEC/EN 62368, IEC/EN 62471
Dimensions	179,00 x 214,00 x 48,00 mm (H x W x D) 8.43 x 7.05 x 1.89 in (H x W x D)
Operating conditions	-25 to +55°C / -13 to 131°F Humidity 10 to 85 % RH (non-condensing)
Scope of delivery	