



5MP Motorized Varifocal Bullet Camera

DS-2CE19H0T-AIT3ZF

SKU: 110787

Product Overview:

Hikvision 5MP Motorized Varifocal Bullet Camera DS-2CE19H0T-AIT3ZF

Features

- High-quality imaging with 5 MP, 2560 - 1944 resolution
- 2.7 mm to 13.5 mm motorized varifocal lens
- Up to 40 m IR distance for bright night imaging
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)

Specifications Camera Image Sensor 5 MP CMOS Signal System PAL/NTSC Resolution 2560 (H) x 1944 (V) Frame Rate TVI: 5 M @ 20 fps, 4 M @ 30 fps, 4 M @ 25 fps, 1080p @ 30 fps, 1080p @ 25 fps AHD: 5 M @ 20 fps, 4 M @ 30 fps, 4 M @ 25fps CVI: 4 M @ 30 fps, 4 M @ 25 fps CVBS: PAL/NTSC Illumination 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR Shutter Time PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s Lens 2.7 mm to 13.5 mm motorized varifocal lens Field of View horizontal FOV: 95° to 26°, vertical FOV: 72° to 20°, diagonal FOV: 126° to 33° Lens Mount 1/4 Day & Night IR Cut Filter WDR (Wide Dynamic Range) Digital WDR Angle Adjustment Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360° Image Day/Night Mode Auto/Color/BW (Black and White) Image Mode STD/HIGH-SAT AGC Yes White Balance Auto/Manual AE (Auto Exposure) Mode DWDR, BLC, HLC, Global Noise Reduction 2D DNR Language English Function Brightness, Smart IR, Sharpness Interface Video Output Switchable TVI/AHD/CVI/CVBS General IR Range Up to 40 m Operating Conditions -40°C to 60°C (-40°F to 140°F), Humidity: 90% or less (non-condensing) Power Supply 12 VDC±15%, 24 VAC±15% Consumption Max 8.8 W Protection Level IP67 Material Front cover: Metal, Main body: Plastic Communication HIKVISION-C Dimension 84.5 mm x 92 mm x 255.1 mm (3.33" x 3.62" x 10.04") Weight Approx. 682 g (1.50 lb.)