



EW-D Charging Set

508862

SKU: 130338 UPC: 615104000000

Versatile and feature-rich digital wireless system for those who sing, speak or play instruments that allow for seamless product pairing and management via the EW-D Smart Assist App. Receive state-of-the-art live sound.

- Fast charging through L 70 USB in combination with the NT 5-20 UCW
- Maximum operating time of 12 hours
- 100% battery power in 3 hours of charging time
- Stackable and charging is through USB-C

Specifications Sennheiser L 70 USB Charger For BA 70 EW-D Transmitter Battery Packs Capacity 2 x Sennheiser BA 70 Rechargeable Batteries Input Voltage 5 V (Typical) Input Current 2 A (Max) Charging Voltage 35 VDC (Nominal) Charging Current 860 mA per Battery Pack (Max) Charging Time 5 Hours (Max) Power Supply NT 5-20 UCW: 100-240 VAC, 50/60 Hz, Universal (Included) Charging Temperature 32 to 122°F / 0 to 50°C Storage Temperature -4 to 158°F / -20 to 70°C Relative Humidity 10 to 95%, Non-Condensing Dimensions 9 x 1.4 x 2.8" / 100 x 35 x 70 mm Weight 3 oz / 86 g Packaging Info Package Weight 765 lb Box Dimensions (LxWxH) 5 x 4.4 x 3.1" Sennheiser BA 70 Rechargeable Battery Pack For EW-D Bodypack And Handheld Transmitters Specs Type Lithium-Ion Capacity 1720 mAh Voltage Nominal: 3.8 V Charging: 4.35 V, Max Charging Time 3 Hours at Room Temperature Temperature Range Charging: 32 to 131°F / 0 to 55°C Discharging: 14 to 131°F / 10 to 55°C Storage: 14 to 113°F / -10 to 45°C Humidity (Relative) Charging/Discharging: 25 to 95%, Non Condensing Storage: 30 to 70%, Non Condensing Dimensions 1 x 1.2 x 0.6" / 54 x 30 x 15 mm Weight 2 oz / 33 g Packaging Info Package Weight 12 lb Box Dimensions (LxWxH) 3 x 2.45 x 1.4" Sennheiser NT 5-20 UCW Universal Power Supply For L 70 USB Battery Charger Specs Input Voltage 100-240 VAC, 50/60 Hz Input Current 25 A at 230 VAC 5 A at 115 VAC Output Voltage 5 VDC Output Current 2 A Standby Power Consumption 75 mW at 230 VDC 75 mW at 115 VDC Operating Temperature 32 to 122°F / -10 to 50°C Storage Temperature -40 to 185°F / -40 to 85°C Relative Humidity 10 to 95%, Non-Condensing Packaging Info Package Weight 485 lb Box Dimensions (LxWxH) 25 x 5.2 x 1.7"