



**HIKVISION®**

Plastic Villa Door Station with card read & 485 & indicators

DS-KV6113-WPE1

SKU: 159229    UPC: 305305494

#### Plastic Villa Door Station with card read & 485 & indicators

- Support Wifi (Only available in DS-KV6113-WPE1 model), convenient setting up and no wiring required
- Support web configuration
- Nice industry design, IP65, 2 indicator integrated;
- Internal Mifare card reader, 1-ch Indoor station access control;
- Noise suppression and echo cancellation
- 2MP HD Camera with IR supplement
- Standard PoE/ 12 VDC

Specifications  
 System parameters Operating system Embedded Linux operation system ROM 16 M, 32 M RAM 256 M  
 CPU Embedded MCU Processor Display parameters Screen size / Operation method / Type / Resolution / Video  
 parameters Lens 1 Resolution Main stream: 1920 x 1080p, 720p Sub stream: 704 x 576 FOV Horizontal: 129° Vertical:  
 75° WDR True WDR Supplement light IR supplement Video compression standard H.264 Audio parameters Audio  
 compression standard G.711 U Audio input Built-in omnidirectional microphone Audio output Built-in loudspeaker Audio  
 compression bitrate 64 Kbps Audio quality Noise suppression and echo cancellation Volume adjustment Adjustable  
 Capacity User capacity / Face capacity / Card capacity / Linked network camera capacity 1 Network parameters  
 Communication protocol TCP/IP, RTSP Wired network 10/100 Mbps self-adaptive Ethernet Wi-Fi standard Support  
 Bluetooth version Not supported. 3G/4G standard / Received frequency 2.4 to 2.4835GHz Transmitted frequency 2.4 to  
 2.4835 GHz Bandwidth 20 to 40 MHz Frequency power 802.11b:16dBm +/- 1.5dBm 802.11g:15dBm +/- 1.5dBm  
 802.11n(ht20):14dBm +/- 1.5dBm 802.11n(ht40):12dBm +/- 1.5dBm Device interfaces Alarm input 4 Network interface 1  
 TAMPER 1 Exit button 1 RS-485 1 USB 0 Wiegand 0 TF card 0 Alarm output 0 Lock control 1 Door contact input 1  
 Power interface 1 Performances Multi-factor authentication 2000 General Button 1 Installation Surface mounting  
 Indicator 2 Weight 265g Protective level IP65 Working temperature -40° C to +55° C(-40° F to 131° F) Working humidity  
 10% to 95% Dimensions 138 mm x 65 mm x 27 mm Battery / Application environment Outdoor Power consumption  
 10 W Language English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Arabic, Turkish,  
 Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian