



24-Port Gigabit Ethernet PoE

561426

SKU: 24248 UPC: 766624000000

24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 4 Gigabit Combo Base-T/SFP Ports IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 370 W, Endspan, 19" Rackmount

Save Installation Time and Money with PoE

The Intellinet Network Solutions 24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 4 Gigabit Combo Base-T/SFP Ports is designed to pass both data and electrical power to a number of PoE-compatible devices via standard Cat5e or Cat6 network cables. Equipped with 24 Gigabit Ethernet ports, all of which support 802.3at/af Power over Ethernet (PoE/PoE+), the switch can power wireless LAN access points and bridges, VoIP (Voice over Internet Protocol) telephones, IP surveillance cameras and more while delivering network speeds of up to 1000 Mbps.

Power over Ethernet 802.3at

The Intellinet Network Solutions 24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 4 Gigabit Combo Base-T/SFP Ports supports the IEEE 802.3at protocol and is designed to inject up to 30 watts of power per port*. IEEE802.3af- or IEEE802.3at-compliant devices attached to the switch require no additional power, which eliminates the time and expense of electrical rewiring and minimizes the unsightly clutter caused by power supplies and adapters. Any mix of PoE and non-PoE devices is supported, and thanks to the switch's built-in short-circuit, overload- and high-voltage-protection functions, your equipment is well-protected. For devices that are not 802.3at/af compliant (e.g., legacy wireless access points or network cameras), we suggest the use of an Intellinet Network Solutions PoE/PoE+ Splitter.

Eliminate Bottlenecks With Gigabit Speeds

Equipped with 24 auto-sensing 10/100/1000 Mbps RJ45 Gigabit Ethernet ports, the Intellinet Network Solutions 24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 4 Gigabit Combo Base-T/SFP Ports offers plenty of performance for your computers, servers and other networking devices. The four shared combo small-form-factor pluggable GBIC module slots (SFP) provide fiber connectivity to achieve even greater distances between network nodes.

Web-Management

This switch is equipped with an impressive array of advanced management functions that allow you to be in full control over your network, even when you are not physically located near it. Your ability to perform critical tasks at a distance makes the switch the perfect network solution for IT and network management professionals.

* Total PoE budget for this switch is 370 watts. Per-port average power distribution is 15.41 watts; maximum per-port power usage cannot exceed 30 watts.

Features

- Provides power and data connection for up to 24 PoE network devices
- Saves installation costs by delivering data and power over existing network cables
- 10/100/1000 Mbps auto-sensing ports automatically detect optimal network speeds
- Console port for configuring via computer

- Four combo small-form-factor pluggable GBIC module slots (SFP) and four RJ45 copper uplinks
- IEEE 802.3at/af-compliant RJ45 PoE/PoE+ output ports
- Power output up to 30 watts per port*
- PoE power budget of 370 watts
- Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (wireless access points, VoIP phones, IP cameras)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- All RJ45 ports equipped with Auto-MDIX and auto-negotiation support
- The Powered Device Monitor feature (PDM) restarts any connected PoE device that fails to respond or send out network traffic.
- Web-based configuration
- Remote reboot/restart
- Supports SNMP management
- Supports VLAN (protocol-based and port-based)
- Supports link aggregation (trunking)
- IGMP Snooping for multicast filtering
- Supports bandwidth control per port
- Supports port mirroring
- Supports two types of QoS: IEEE 802.1p and DSCP
- Broadcast storm control with multicast packet rate settings
- Supports jumbo frames up to 9.6 kBytes
- Store and forward switching architecture
- Full/half duplex operation
- IEEE 802.3x flow control for full duplex
- Supports 8k MAC address entries
- LEDs for power, link/activity and PoE
- Two high-volume cooling fans to ensure perfect ventilation
- Includes 19" rackmount brackets
- Three-year warranty

Standards IEEE 802.1p (Traffic Prioritization) IEEE 802.1q (VLAN Tagging) IEEE 802.1w (Rapid Spanning Tree Protocol) IEEE 802.3ad (Link Aggregation) IEEE 802.3 (10Base-T Ethernet) IEEE 802.3ab (Twisted Pair Gigabit Ethernet) IEEE 802.3ad (Link Aggregation Control Protocol LACP) IEEE 802.3af (Power over Ethernet 802.3at Type 1) IEEE 802.3at (Power over Ethernet 802.3at Type 2) IEEE 802.3u (100Base-TX Fast Ethernet) IEEE 802.3x (flow control, for full duplex mode) Packet filter/forwarding rate: 1,488,000 pps (1000 Mbps) 148,800 pps (100 Mbps) 14,880 pps (10 Mbps) MAC address table: 8k Buffer memory: 4.1Mb Backplane speed / switch fabric: 56 Gbps Switch architecture: store and forward Configuration Options: Port link speed: 10 Mbps, 100 Mbps, 1000 Mbps or auto-negotiation PoE on/off per port Flow control on/off per port VLAN Rate limiting (ingress rate and egress rate) Port Mirroring Port Aggregation / LACP: 8 groups Broadcast Storm configuration with broadcast rate, multicast rate, and flooded unicast rate IGMP Snooping Quality of Service (QoS): IEEE 802.1p or DSCP Integrated VeriPHY cable diagnostics tool Integrated ICMP Ping client sends ping requests to other network nodes SNMPv1/v2c (Simple Network Management Protocol) LAN settings (IP address, Gateway, etc.) Certifications: FCC Class A, CE LEDs PoE Power Link/activity Power Input: 90 - 240 V AC, 50 - 60 Hz Power consumption: 431.7 watts (maximum) Environmental Metal housing Dimensions: 330 (L) x 440 (W) x 44 (H) [mm] / 12.99 (L) x 17.32 (W) x 1.73 (H) [in] Weight: 4.7 kg (10.36 lbs.) Operating temperature: 0 - 45°C (32 - 113°F) Storage temperature: -40 - 70°C (-40 - 158°F) Operating humidity: 10 - 90% RH, non-condensing Package Contents 24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 4 Gigabit Combo Base-T/SFP Ports Quick Instruction Guide Power cable 19" mounting brackets Rubber feet