



Surface Mount IP Video Intercom - Stainless Steel

423871601

SKU: 146076 UPC: 4260423871601

DoorBird is the smart solution for your house entrance. Simply connect your DoorBird IP Video Door Station to your smartphone and talk to your visitor – anywhere you are. The IP Video Door Station can be used as a stand-alone unit or can be integrated into an existing Smart Home platform. Even existing classic installations such as an electric door opener can still be used and controlled via the DoorBird App.

Features

- Intercom with camera including keypad
- WiFi / LAN connection (PoE capable)
- Surface-mounting housing included
- 2-way audio
- Ultra-wide angle lens, 1080p, night vision, IR LEDs
- 4D motion sensor
- Intercom with 1 freely configurable bistable switching relay

For single-family homes and businesses with 1 unit, 1 call button

Stainless steel V2A, brushed

GENERAL

- Front panel
- 3 mm (0.12 in)
- For further materials and colours see material board and Online Shop.
- Mounting housing
- (backbox) Polycarbonate
- Mounting type Surface-mounted,
- flush-mounted version sold separately
- Call button Illuminated
- Nameplate Plastic
- see www.doorbird.com/buy
- Keypad Module
- 12 keys, illuminated, configurable via App, e.g.
 - Individual PIN codes
 - Individual events (e.g. switch a relay,
- HTTP(s) request)
 - Individual schedules
 - Up to 500 PIN codes manageable
- Power supply 15 V DC (max. 15 W) or Power over
- Ethernet (PoE 802.3af Mode-A)
- Weight 920 g
- Connectors
 - LAN/PoE (T+, T-, R+, R-)
 - Bistable latching relay, max. 1-24 V DC/AC,

- 1 A, e.g. for electric door opener
 - External input for external door opener button
 - 15 V DC input (+, -), max. 15 W
- Weatherproof Yes, IP65
- Approvals CE, UKCA, FCC, IC, RoHS, REACH, WEEE, Wi-Fi
- CERTIFIED™
- Dimensions 65,00 x 241,00 x 29,50 mm (H x W x D)
- 56 x 9.49 x 1.16 in (H x W x D)
- Operating conditions
- -25 to +55°C / -13 to 131°F
- Humidity 10 to 85 % RH
- (non-condensing)
- Scope of delivery
- 1x Main Electrical Unit
- 1x Front panel
- 1x Surface-mounting housing (backbox)
- 1x Power supply unit (mains adaptor) with up
- to 4 country-specific outlet adaptors
- (110 - 240 V AC to 15 V DC)
- 1x RJ45 adapter
- 1x Screwdriver
- 1x Quickstart guide with Digital Passport
- 1x Installation manual
- 1x Small parts