



## 19"• Patch Panel 48-Ports RJ45 with Lacing Bar

PP3-19-48-8P8C-C6-110-LB

SKU: 24944    UPC: 809380000000

Hyperline 19 Patch Panel 48 ports RJ45 with Lacing Bar PP3-19-48-8P8C-C6-110-LB: The standard size of 19" for installation in telecommunication cabinets and racks for Horizontal terminations. Designed for 22-26 AWG solid conductors with the following dimensions.

Height: 1U (12, 16 and 24 ports), 2U (32 and 48 ports)

### Features

- It is used for switching single-core cables sizes 22 - 24 AWG (0,64 - 0,51 mm) The compact design is ideal for data centers and high-density connections. Shielded enclosure protects against noise and interference
- Color marking of conductors according to T568Band T568A; Numeral marking of ports on the front side of the panel
- Space for additional marking; Color and numeral marking of IDC modules on the rear side of the panel 110 type punch down tool is used for cable termination
- Meets ANSI/TIA/EIA-568-C Category 6 requirements
- Meets TIA/EIA TSB-40; Meets ISO/IEC Generic Cabling Standard 11801; Meets CENELEC Generic Cabling Standard EN50173

Specifications: Maximum current (at 20 ° C): 1.5 A DC Resistance 0.1 mOhm (max.) | Contact Resistance 20 mOhm Insulation Resistance 500 MOhm Dielectric Withstand Voltage 1000 V AC RMS, 60Hz/1min Front Plate : Fireproof ABS UL-94V0; IDC: Phosphor Bronze and Fireproof UL-94V0 PCT(PC+PBT) PCB: FR-4 / UL-94V0 / 1.6mm; Contacts: Phosphor Bronze 8P8C & 50 micro inches gold plated; Metal housing: Metal (SPCC) 1.6mm 19" Patch panel, 48 ports RJ45, category 6, 110 IDC with Lacing Bar