



## D1101V Surface-Mount IP Video Intercom - Stainless Steel

423866751

SKU: 65351    UPC: 4260423866751

A modern doorbell for home or office and stylish member of the brand new family of Doorbirds. As well as a refined and sophisticated look, this model introduces some new functionality. Such as Bluetooth for access control (future firmware update), 1080p Camera, Sony image sensor, and improved audio quality. And it looks so elegant!

For single-family houses and commercial buildings with 1 unit1 Call Button

### Features

- Video intercom including surface-mounting housing
- WiFi / LAN connection (PoE capable)
- 2-way audio
- Ultra-wide angle lens, 1080p, night vision, IR LEDs
- 4D motion sensor
- Intercom with 1 freely configurable bistable switching relay

<b>Front Panel</b>	3 mm (0.12 in) For further materials and colours see material board and Online Shop.
<b>Mounting Housing (backbox)</b>	Polycarbonate
<b>Mounting Type</b>	Surface-mounted, flush-mounted version sold separately
<b>Call button</b>	Illuminated
<b>Nameplate</b>	Plastic Metal cover plate and engraving available separately
<b>Power supply</b>	15 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)
<b>Weight</b>	405 g
<b>Connectors</b>	LAN/PoE (T+, T-, R+, R-) <ul style="list-style-type: none"> <li>• Bistable latching relay, max. 1-24 V DC/AC, 1 A, e.g. for electric door opener</li> <li>• External input for external door opener button</li> <li>• 15 V DC input (+, -), max. 15 W</li> <li>• Relays can be expanded / detached with DoorBird I/O Door Controller</li> </ul>
<b>Protection Class</b>	IP65, IK08
<b>Approvals</b>	CE, UKCA, FCC, IC, RoHS, REACH, WEEE, Wi-Fi CERTIFIED™

<b>Dimensions</b>	151,9 x 65 x 32 mm (H x W x D) 5.98 x 2.56 x 1.26 in (H x W x D)
<b>Operating Conditions</b>	-25 to +55°C / -13 to 131°F Humidity 10 to 85 % RH (non-condensing)