



4x2 HDBaseT Matrix Kit -70m

HMXL42ARC-KIT

SKU: 128988 UPC: 9340240000000

Our Essential 4x2 HDBaseT™ Matrix offers unprecedented performance and value for the custom installation market.

The HMXL42ARC-KIT is a HDMI2.0 4K60Hz 4:4:4 HDCP2.2 Matrix package utilising CSC technology to deliver HDMI, Bi-directional IR and PoC up to lengths of 70m over a single CAT cable.

The Matrix also provides advanced features including simultaneous HDBaseT™/HDMI on output 1, video Smart Scaling on HDBaseT outputs, manual or auto source selection, independent audio matrix and a web browser interface module for control and configuration of the Matrix.

The HMXL42ARC-KIT is supplied with 2 x HDBaseT™ receivers.

Features

- Matrix Switcher with Audio De-Embedding
- 4 x HDMI Inputs, 2 x HDBaseT Outputs
- 2 x Analog & Optical Digital Outputs
- 2 x ARC from Zone Outputs
- Supports up to UHD 4K60 4:4:4
- HDCP 2.2 Compliance & HDR Support
- Supports All Known HDMI Audio Formats
- Front Panel/IR/RS-232/TCP/IP Control
- HDCP 2.2 Compliant
- 2 x RX70CS HDBaseT Receivers Included

Specifications Video Input Connectors: 4x HDMI Type A, 19-pin, female Video Output Connectors: 1x HDMI Type A, 19-pin, female, 2x HDBaseT RJ45 connector Audio Output Connectors: 2x Analogue audio L/R (3.5mm stereo Jack), 2x Optical (SPDIF) RS-232 Serial Ports: 1x 3-pin Phoenix connector TCP/IP Control: 1x RJ45, female IR Input Ports: 3x 3.5mm stereo jack IR Output Ports: 4x 3.5mm mono jack Rack Mountable: 1U rack height, rack ears included Casing Dimensions (WxDxH): 220mm x 235mm x 44mm (without feet) Shipping Weight: 4.5kg Operating Temperature: 32°F to 104°F (0°C to 40°C) Storage Temperature: -4°F to 140°F (-20°C to 60°C) Power Supply: 1x 24V/5A DC