



## D2108V Multi-Tenant IP Video Door Intercom Station

423867062

SKU: 147494    UPC: 4260423865389

DoorBird D2108V IP Video Door Intercom Station. Intercom system for multi-tenant buildings and businesses with 8 units. Comes with 8 call buttons.

### Features

- Surface- and flush-mount possible, housings sold separately
- LAN connection (PoE capable)
- 2-way audio
- Intercom with ultra-wide angle lens, 720p, night vision, 12 IR LEDs
- 4D motion sensor, RFID reader
- Intercom with 2 freely configurable bistable switching relays
- Stainless steel V2A, brushed

<b>Front Cover</b>	3 mm (0.12 in) For further information on materials and colours see the materials table on the product page in the online shop.
<b>Mounting Type</b>	Flush or surface mount, Mounting backing case available separately
<b>Call Button</b>	Illuminated
<b>Nameplate</b>	Plastic Metal cover plate and engraving available separately
<b>Power supply</b>	15 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)
<b>Connections</b>	<ul style="list-style-type: none"> <li>• RJ45, for LAN/PoE</li> <li>• Bistable self-latching relay #1, max. 24 V DC/AC, 1 Ampere, e.g. for electrical door opener</li> <li>• Bistable self-latching relay #2, max. 24 V DC/AC, 1 Ampere, e.g. for electrical door opener</li> <li>• External input for external door opening button</li> <li>• 15 V DC input (-/+), max. 15 W</li> <li>• Relay can be extended/replaced with DoorBird I/O Door Controller.</li> </ul>

<b>Protection class</b>	IP65, IK08
<b>Approvals</b>	CE, FCC, IC, UKCA, RoHS, REACH, WEEE, IEC/EN 62368, IEC/EN 62471
<b>Operating conditions</b>	-25 °C to +55 °C / -13 °F to 131 °F Relative air humidity 10% to 85% (non-condensing)