



18 Output CCTV Power Supply

SAV182D

SKU: 783 UPC: 782240000000

Sav182D Power Supply provides 12VDC distributed via eighteen (18) Class 2 Rated PTC protected power limited outputs for powering surveillance cameras.

Features

- Power LEDs.
- Field installable 3-wire line cord with integral strain relief.
- Unit maintains camera synchronization.
- Ease of installation saves time & eliminates costly labor.
- 12VDC @ 11A total output current (0.61A per device, 2.5A max.).
- Eighteen (18) Class 2 Rated PTC protected power limited auto-resettable outputs.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.

Input: 115VAC 60Hz, 3 amp /230VAC 50Hz, 1.5 amp. Output: 12VDC @ 11 amp total output current (0.61 amp per device, 2.5 amp max.). Eighteen (18) Class 2 Rated PTC protected powerlimited outputs. Filtered and electronically regulated outputs. Short circuit and thermal overload protection. Electrical: Operating temperature: 0Â° C to 49Â° C ambient. 68.24 BTU/Hr. System AC input VA requirement: - 115VAC: 345VA.; - 230VAC: 330VA Mechanical: NEMA1 enclosure. Enclosure Dimensions (H x W x D approx.): 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm). Product weight (approx.): 7.8 lbs. (3.54 kg). Shipping weight (approx.): 8.7 lbs. (3.95 kg).