



## D1101V Flush-Mount IP Video Intercom - Graphite Black

423874107

SKU: 141498    UPC: 4260423874107

A modern doorbell for home or office and stylish member of the brand new family of Doorbirds. As well as a refined and sophisticated look, this model introduces some new functionality. Such as Bluetooth for access control (future firmware update), 1080p Camera, Sony image sensor, and improved audio quality. And it looks so elegant!

For single-family houses and commercial buildings with 1 unit1 Call Button

### Features

- Video intercom including flush-mounting housing
- WiFi / LAN connection (PoE capable)
- 2-way audio
- Ultra-wide angle lens, 1080p, night vision, IR LEDs
- 4D motion sensor
- Intercom with 1 freely configurable bistable switching relay

|                                   |  |
|-----------------------------------|--|
| <b>Front Panel</b>                | 3 mm (0.12 in),<br>For further materials and colours see material board and Online Shop.   |
| <b>Mounting Housing (backbox)</b> | Stainless steel  |
| <b>Mounting Type</b>              | Flush-mounted,<br>surface-mounted version sold separately  |
| <b>Call button</b>                | Illuminated  |
| <b>Power supply</b>               | 15 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)  |
| <b>Weight</b>                     | 570 g  |
| <b>Connectors</b>                 | <ul style="list-style-type: none"> <li>• LAN/PoE (T+, T-, R+, R-)</li> <li>• Bistable latching relay, max. 1-24 V DC/AC, 1 A, e.g. for electric door opener</li> <li>• External input for external door opener button</li> <li>• 15 V DC input (+, -), max. 15 W</li> <li>• Relays can be expanded / detached with DoorBird I/O Door Controller</li> </ul> |
| <b>Protection Class</b>           | IP65, IK08   |
| <b>Approvals</b>                  | CE, UKCA, FCC, IC, RoHS, REACH, WEEE, Wi-Fi CERTIFIED™   |
| <b>Dimensions</b>                 | 171.9 x 85 x 32 mm (H x W x D)<br>6.77 x 3.35 x 1.26 in (H x W x D)  |

**Operating Conditions**

-25 to +55°C / -13 to 131°F Humidity 10 to 85 % RH (non-condensing)

**Scope of Delivery**

1x Main Electrical Unit  
1x Front panel  
1x Flush-mounting housing (backbox)  
1x Power supply unit (mains adaptor) with up  
to 4 country-specific outlet adaptors  
(100 - 240 V AC to 15 V DC)  
1x RJ45 adapter  
1x Screwdriver  
1x Quickstart guide with Digital Passport  
1x Installation manual  
1x Small parts