



## Slimline HDBaseT Receiver - 70m

HEX70SL-RX

SKU: 129017    UPC: 9340240000000

The HEX70SL-RX 4K HDBaseT™ Receiver offers market leading features in a slimline chassis.

The product delivers HDMI, Bi-directional IR and Bi-directional PoC up to lengths of 70m.

### Features

- Advanced HDBaseT™ technology offering uncompressed video and audio with zero latency
- Enhanced slimline chassis
- Extends HDMI 1080p up to a distance of 70m over a single CAT cable
- Supports 4K UHD video up to 40m (3840 x 2160 @ 30Hz 4:4:4, 4096 x 2160 @ 24Hz 4:4:4, and 4K @ 60Hz 4:2:0)
- Supports all industry standard video resolutions including VGA-WUXGA and 480i-4K
- Supports all known HDMI audio formats including Dolby TrueHD, Dolby Atmos, Dolby Digital Plus and DTS-HD
- Master Audio transmission
- Bi-directional IR pass-through
- Supports bi-directional PoC (Power over Cable) to power, or be powered from, a compatible transmitter point (power supply not included)
- HDCP 2.2 compliant

Specifications Video Input Connectors: 1 x HDBaseT RJ45 connector Video Output Connectors: 1 x HDMI Type A, 19-pin, female IR Input Ports: 1 x 3.5mm stereo jack IR Output Ports: 1 x 3.5mm mono jack Power Supply: 12V/1A DC Dimensions (L x W x H): 106mm x 73mm x 16mm Shipping Weight: 0.8kg Operating Temperature: 32°F to 104°F (-5°C to +55°C) Storage Temperature: -4°F to 140°F (-25°C to +70°C)"