



## D2101KH Single-Family IP Video Door Intercom

423869967

SKU: 65468    UPC: 4260423868960

DoorBird D2101KH Intercom system for single-family homes and businesses with 1 unit, 1 call button

### Features

- Surface- and flush-mount possible, housings sold separately
- LAN connection (PoE capable)
- 2-way audio
- Ultra-wide angle lens, 720p, night vision, 12 IR LEDs
- 4D motion sensor, RFID reader
- Keypad
- Intercom with 2 freely configurable bistable switching relays

<b>Front Panel</b>	3 mm (0.12 in) Available in brushed stainless steel V2A / V4A and V2A with bronze and titanium finish, DB 703, RAL 7016, Graphite Black (Raven Polar)
<b>Mounting Type</b>	Flush- or surface-mounted, mounting housing sold separately
<b>Call Button</b>	Illuminated
<b>Nameplate</b>	Stainless Steel, Bell symbol, engraved through material for illumination, self-adhesive. Engravable metal nameplate sold separately
<b>Power supply</b>	15 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)
<b>Info Module</b>	3.5", illuminated
<b>Keypad Module</b>	12 keys, illuminated, configurable via App, e.g. <ul style="list-style-type: none"> <li>• Individual PIN codes</li> <li>• Individual events (e.g. switch a relay, HTTP(s) request)</li> <li>• Individual schedules</li> <li>• Up to 500 PIN codes manageable</li> <li>• 30 most recent entries viewable in history</li> </ul>
<b>Weight</b>	2510 g

<b>Connectors</b>	<ul style="list-style-type: none"> <li>• RJ45, for LAN/PoE</li> <li>• Bistable latching relay #1, max. 24 V DC&amp;hairsp;/&amp;hairsp;AC, 1 Ampere, e.g. for electric door opener</li> <li>• Bistable latching relay #2, max. 24 V DC&amp;hairsp;/&amp;hairsp;AC, 1 Ampere, e.g. for electric door opener</li> <li>• External input for external door opener button</li> <li>• 15 V DC input (+, -), max. 15 W</li> <li>• Relays can be expanded / detached with DoorBird I/O Door Controller</li> </ul>
<b>Weatherproof</b>	Yes, IP65
<b>Approvals</b>	IP65, CE, FCC, IC, RoHS, IK08, REACH, IEC/EN 62368, IEC/EN 62471
<b>Dimensions</b>	256 x 275,25 x 48,75 mm (H x W x D) 10,08 x 10,13 x 1,92 in (H x W x D)
<b>Operating conditions</b>	-25 to +55°C / -13 to 131°F Humidity 10 to 85 % RH (non condensing)