



5MP HD ColorHunter Fixed Eyeball Network Camera

IPC3615SE-ADF28KM-WLI0-BK

SKU: 113509

High-quality image with 5MP, 1/2.7" CMOS sensor 5MP (2880*1620)@25fps; 4MP (2560*1440)@25fps; 3MP (2304*1296)@25fps; 2MP (1920*1080)@ 30/25fps; Ultra 265, H.265, H.264, MJPEG Colorhunter technology ensures 24-hour full-color images 120dB true WDR technology enables clear image in the strong light scene Support 9:16 corridor Mode Support built-in Mic Support 256 G Micro SD card IP67 protection Support PoE power supply.

Features

- High-quality image with 5MP, 1/2.7" CMOS sensor
- 5MP (2880*1620)@30/25fps; 4MP (2560*1440)@30/25fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@ 30/25fps;
- Ultra 265, H.265, H.264, MJPEG
- Colorhunter technology ensures 24-hour full-color images
- 120dB true WDR technology enables clear image in strong light scene
- Support 9:16 corridor Mode
- Support built-in Mic
- Support 256 G Micro SD card
- IP67 protection
- Support PoE power supply

Camera Sensor 1/2.7" 5.0 megapixel, progressive scan, CMOS Lens 2.8mm@F1.0 4.0mm@F1.0 DORI Distance Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 63.0 25.2 12.6 6.3 4.0 90.0 36.0 18.0 9.0 Angle of view(H) 102.0° 80.2° Angle of View (V) 53.4° 43.0° Angle of View (O) 121.0° 94.7° Adjustment angle Pan: 3°~ 360° Tilt: 0°~ 80° Rotate: 3°~ 360° Shutter Auto/Manual, 1 ~ 1/100000s Minimum Illumination Colour: 0.001Lux (F1.0, AGC ON) S/N >56dB Defog Digital Defog WDR 120dB LEDs Number 2 LED Distance Up to 30m (98ft) Video Video Compression Ultra265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main profile, High profile Frame Rate Main Stream: 5MP (2880*1620), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 2MP (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF (704*288), Max 30fps; CIF (352*288), Max 30fps; Third Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF (704*288), Max 30fps; CIF (352*288), Max 30fps; Video Bit Rate 128 Kbps~16 Mbps 9:16 Corridor Mode Supported OSD Up to 8 OSDs Privacy Mask Up to 4 areas ROI Up to 8 areas Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital noise reduction 2D/3D DNR Smart Illumination Support Flip Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise Dewarping N/A HLC Support BLC Support Audio Audio Compression G.711 Suppression Supported Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256GB Network Storage ANR, NAS(NFS) Network Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS Compatible Integration ONVIF (Profile S, Profile G, Profile T), API Client EZStation, EZView, EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below; Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Interface Built-in Mic Supported Network 1 RJ45 10M/100M Base-TX Ethernet Certifications Certifications CE: EN 60950-1, UL: UL60950-1 FCC: FCC Part 15 General Power DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 7.5W Dimensions (W x H) 110.5 x 94.1mm (4.4" x 3.7") Net Weight 0.44kg (0.97lb) Material metal Working Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 5%~95% RH (non-condensing) Storage Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 5%~95% RH (non-condensing) Surge protection 2KV Ingress Protection IP67