



6 x 4MP Turret IP Camera + 8-Channel NVR + 2TB HDD Video Surveillance Kit

EK-S31P8T46T2

SKU: 143231

Uniview EK-S31P8T46T2 6 x 4MP Turret IP Camera + 8-Channel NVR + 2TB HDD Video Surveillance Kit

Features

- NVR301-08S3-P8
 - Support Ultra 265/H.265/H.264 video formats
 - 8-channel input
 - Plug & Play with 8 independent PoE network interfaces
 - Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T
 - Support 1-ch HDMI, 1-ch VGA
 - HDMI and VGA simultaneous output
 - Up to 8MP resolution recording
 - 1 SATA HDD
 - Support cloud upgrade
- EC-T4F28M-V3
 - Day/night functionality
 - Smart IR, up to 30 m (98 ft) IR distance
 - 2D/3D DNR (Digital Noise Reduction)
 - Ultra 265, H.265, H.264, MJPEG
 - ROI (Region of Interest)
 - ONVIF Conformance
 - Wide temperature range: -30°C ~ +60°C (-22°F ~ 140°F)
 - Wide voltage range of ±25%
 - IP66

Specifications
 Model NVR301-08S3-P8
 Video/Audio Input IP Video Input 8-ch
 Network Incoming Bandwidth 64Mbps
 Outgoing Bandwidth 48Mbps
 Remote Users 128
 Protocols TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP
 Video/Audio Output HDMI/VGA Output
 HDMI: 3840x2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
 VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
 Recording Resolution 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 Audio Output 1-ch, RCA
 Audio Compression G.711A, G.711US
 Synchronous Playback 8-ch
 Corridor Mode Screen 3/4/5/7/9
 Decoding Decoding format Ultra 265/H.265/H.264
 Liveview/Playback 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 Capability 1 x 4k@30, 1 x 5MP@30, 2 x 4MP@30, 4 x 3MP@25, 4 x 1080p@30, 8 x 720p@30
 Hard Disk SATA 1 SATA interface
 Capacity of up to 8TB for each disk
 Smart