



Turret IP Camera Kit 4MP 4 Channel

EK-S31P4T44T1

SKU: 129258

UNV's 4-channel camera kit has everything you need, except a monitor, to put a surveillance system into your home or business. This system incorporates 4MP high-resolution cameras to give you a great image. Just run the included ethernet cable to where you want the cameras located plug everything in and the NVR will automatically detect and configure the cameras. To view the system remotely, you just need to install the EZView app, register for a free account, and scan a QR code from the NVR's network menu - no messing with your router or port forwarding required.

Features

- 4MP max resolution (2560*1440), up to 20fps
- Smart IR rated for up to 30M (98ft)
- Ultra H.265 Compression
- 4 Channel NVR with built-in PoE for Plug and Play setup
- Security-rated hard drive designed for the demanding 24/7 use of CCTV
- IP67 waterproof-rated cameras for outdoor use

Model NVR301-04S3-P4 Video/Audio Input IP Video Input: 4-ch Network Incoming Bandwidth: 64Mbps Outgoing Bandwidth: 48Mbps Remote Users: 128 Protocols: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SMTP, RTSP Video/Audio Output HDMI/VGA Output HDMI: 4K(3840x2160)/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz Recording Resolution 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Audio Output 1-ch, RCA Audio Compression 711A, G.711U Synchronous Playback 4-ch Corridor Mode Screen 3/4 Decoding Decoding format: Ultra 265/H.265/H.264 Liveview/Playback: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Capability: 1 x 4K@30, 4 x 5MP@25, 4 x 4MP@25, 4 x 3MP@25, 4 x 1080p@30 Hard Disk SATA: 1 SATA interface Capacity: up to 8TB for each disk Smart VCA Detection by Camera: Face detection, Intrusion detection, Cross line detection, Audio detection, Enter Area, Leave Area VCA Search: Face Search, Behavior Search External Interface Network Interface: 1 RJ45 10M/100M self-adaptive Ethernet Interface USB Interface: Rear panel 1 x USB2.0 PoE Interface: 4 RJ-45 10M/100M self-adaptive Ethernet Interface Max Power: Max 30W for single port Max 54W in total Supported Standard: IEEE 802.3at, IEEE 802.3af General Power Supply: 48V DC Power Consumption: 9 W (without HDD) Working Environment: -10°C ~ + 55°C (+14°F ~ +131°F), Humidity 0% ~ 90% RH(non-condensing) Dimensions(WxDxH) : 260mm x 240mm x 46 mm (10.2" x 9.4" x 1.8") Weight (without HDD) 1.1kg (2.43lb)