



## 5MP ColorHunter HD Fixed Mini Bullet Analog

UAC-B125-AF28M-W

SKU: 143246

UAC-B125-AF28(40)M-W is a 5MP ColorHunter HD fixed mini bullet analog camera with a high-performance 1/2.7-inch CMOS sensor. It supports TVI/AHD/CVI/ CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types, the camera can achieve low-cost, long-distance, anti-interference megapixel HD video transmission without time delay. It supports audio input, synchronous transmission of audio and video, and provides 24/7 color images

### Features

- 5MP high-quality imaging
- TVI/AHD/CVI/ CVBS
- Supports white light illumination, 24/7 color images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high-quality audio transmission via coaxial cables
- Metal front face and housing

Sensor Pixel 5MP Size 1/2.7" Minimum illumination 0.05 lux (F1.4, AGC ON) 0 lux (white light on) Lens Lens 2.8mm 4.0mm Lens mount M12 Angle of view H: 111.5° V: 58.9° D: 134.8° H: 89.6° V: 48.3° D: 106.4° Illuminator Illuminator Two white-light illuminators Illumination distance 40m Lifetime ≥60,000 hours Video Resolution 5MP@25fps: 2880(H)x1620(V); 5MP@20fps: 2592(H)x1944(V); 5MP@12.5fps: 2592(H)x1944(V) 4MP: 2560(H)x1440(V) 1080P: 1920(H)x1080(V) Frame rate TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC Shutter time PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s Image Exposure mode Four modes: Global (default), BLC, HLC, DWDR Day/Night 24/7 color images Digital noise reduction 2D White balance Two modes: Auto (default), Manual WDR DWDR Flip Supports 180° horizontal flip, 180° vertical flip Audio Microphone Built-in Mic Camera audio TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps Interface Power 5.5mm power interface Video output BNC, supports TVI/AHD/CVI/ CVBS Operating environment Temperature -30°C to 60°C (-22°F to 140°F) Humidity ≤95% (RH, non-condensing) Surge protection 4kV Ingress protection IP67 General Power DC12V (±25%), with reverse polarity protection and surge protection. Max 3.28W Mount 3D bracket supplied, surface mount (default), optional junction box Dimensions 157.4mm\*66.5mm\*66.5mm (L\*W\*H) Material Metal Weight 279g (0.62lb) Certification CB, CE, FCC, UL