



## 4MP HD ColorHunter Fixed Eyeball Network Camera

IPC3624LE-ADF28K-WL

SKU: 147021

### 4MP HD ColorHunter Fixed Eyeball Network Camera Features

- High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
- 4MP (2688\*1520) @ 25/20fps; 4MP (2560\*1440) @ 25/20fps; 3MP (2304\*1296) @ 30/25fps; 2MP (1920\*1080) @ 30/25fps;
- Ultra 265, H.265, H.264, MJPEG
- Colorhunter technology ensures 24-hour full-color images
- 120dB true WDR technology enables clear image in strong light scene
- Support 9:16 Corridor Mode
- Built-in Mic
- White Light, up to 30m white light distance
- Supports 128 GB Micro SD card
- IP67 protection
- Support PoE power supply
- 3-Axis

IPC3624LE-ADF28K-WL IPC3624LE-ADF40K-WL Camera Sensor : 1/1.8", 4.0 megapixel, progressive scan, CMOS Minimum Illumination: Colour: 0.0005lux (F1.0, AGC ON) Shutter: Auto/Manual, 1 ~ 1/100000s Adjustment angle: Pan: 0° ~ 360° Tilt: 0° ~ 75° Rotate: 0° ~ 360° WDR: 120dB S/N: >52dB Lens Lens: 2.8mm @ F1.0 0mm @ F1.0 Iris: Fixed Field of View (H): 110.4° 4° Field of View (V): 60.5° 2° Field of View (D): 115.2° 7° DORI DORI Distance : Lens (mm) Detect 1/4" ~ 1/4" Observe 1/4" ~ 1/4" Recognize 1/4" ~ 1/4" Identify 1/4" ~ 1/4" 2.8: 43.4(142.5ft) 17.4(57.0ft) 8.7(28.5ft) 4.3(14.3ft) 4.0: 62.1(203.6ft) 24.8(81.5ft) 12.4(40.7ft) 6.2(20.4ft) Illuminator LED Distance: Up to 30m (98ft) LEDs Number: 2 LED On/Off Control: Auto/Manual Video Video Compression: Ultra265, H.265, H.264, MJPEG 264 code profile: Baseline profile, Main profile, High profile Frame Rate: Main Stream: 4MP (2688\*1520), Max 25fps; 4MP (2560\*1440), Max 25fps; 3MP (2304\*1296), Max 30fps; 1080P (1920\*1080), Max 30fps; Sub Stream: 720P (1280\*720), Max 30fps; D1 (720\*576), Max 30fps; 640\*360, Max 30fps; Video Bit Rate: 128 Kbps~6144Kbps U-code: Support OSD: Up to 4 OSDs Privacy Mask: Up to 4 areas ROI: Up to 8 areas Video Stream: Dual streams Image White Balance: Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto 2 Digital noise reduction: 2D/3D DNR Smart Illumination: Support Flip: Normal/Vertical/Horizontal/180°/90° Clockwise/90° Anti-clockwise Dewarping: N/A HLC: Support BLC: Support Defog: Digital Defog Events Basic Detection: Cross line, intrusion (based on human body detection), Motion detection, Tampering alarm, Audio Detection General Function: Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP authentication Audio Audio Compression: G.711U, G.711A Audio Bitrate: 64 Kbps Two-way audio: N/A Suppression: Support Sampling Rate: 8KHZ Storage Edge Storage: Micro SD, up to 128GB Network Storage: ANR, NAS(NFS) Network Protocols: IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, QoS, RTMP, SSL/TLS Compatible Integration: ONVIF (Profile S, Profile G, Profile T), API, SDK User/Host: Up to 32 users. 2 user levels: administrator and common user Security: Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF Client EZStation EZView EZLive Web Browser: Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above Interface Audio I/O: N/A Alarm I/O: N/A Serial Port: N/A Built-in Mic: Support Built-in Speaker: N/A WIFI: N/A Network: 1 \* RJ45 10M/100M Base-TX Ethernet Video Output: N/A Certifications EMC : CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part 15 B) Safety: CE LVD (EN 62368-1) CB (IEC 62368-1) UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1) Environment :

CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)Protection: IP67 (IEC 60529)GeneralPower: DC 12V±25%, PoE (IEEE 802.3af)Power consumption: Max 5.9WPower Interface: 5.5mm coaxial power plugDimensions (W x H) : 118x106mm (4.6" x 4.2")Weight: 0.45kg(0.99lb)Material: Metal + PlasticWorking Environment: -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)Storage Environment: -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)surge protection: 4KVReset Button: Support