



4MP HD IR Fixed Turret IP Camera

IPC3614SR3-ADF28KMC-DL

SKU: 133015

Uniview 4MP HD IR Fixed Eyeball Network Camera (Only for USA) IPC3614SR3-ADF28KMC-DL

Features

High quality image with 4MP, 1/3"CMOS sensor
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Lighthunter technology ensures high image quality in low illumination environment
120dB true WDR technology enables clear images in the strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

Specifications IPC3614SR3-ADF28K-G IPC3614SR3-ADF40K-G Camera Sensor 1/3"4.0 megapixel, progressive scan, CMOS Lens 2.8mm@F1.6 4.0mm@F1.6 DORI Distance Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 63.0 25.2 12.6 6.3 4.0 90.0 36.0 18.0 9.0 Angle Of View (H) 101.1° 83.7° Angle Of View (V) 55.3° 44.9° Angle Of View (O) 111.1° 89.2° Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 80° Rotate: 0° ~ 360° Shutter Auto/Manual, 1 ~ 1/100000s Minimum Illumination Support LightHunter: Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR Day/Night IR-cut filter with auto switch (ICR) Digital noise reduction 2D/3D DNR S/N >56dB IR Range Up to 30m (98ft) IR range Wavelength 850nm IR On/Off Control Auto/Manual Defog Digital Defog WDR 120dB Video Video Compression Ultra 265, H.265, H.264, MJPEG H.264 Code Profile Baseline profile, Main profile, High profile Frame Rate Main Stream: 4MP (2688*1520), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; Video Bit Rate 128 Kbps~16 Mbps 9:16 Corridor Mode Supported OSD Up to 4 OSDs Privacy Mask Up to 4 areas ROI Up to 8 areas Motion Detection Up to 4 areas Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital noise reduction 2D/3D DNR Smart IR Supported Flip Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise Dewarping N/A HLC Supported BLC Supported Smart Behavior Detection Cross line, intrusion(based on human body detection) motion detection, tampering alarm, audio detection General Function Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication, HTTP authentication Network Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP Compatible Integration ONVIF (Profile S, Profile G, Profile T), API Client EZStation EZView EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Audio Audio Compression G.711 Suppression Supported Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256 GB Network Storage ANR,NAS(NFS) Interface Network 10/100M Base-TX Ethernet Built-in Mic Supported Certifications Certifications UL: UL60950-1 FCC: FCC Part 15 General Power DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 6.0W Dimensions (Å x H) 110.5 x 94.1mm (4.4" x 3.7") Net Weight 0.43kg (0.95lb) Material Metal Working Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 5%~95% RH (non-condensing) Storage Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 5%~95% RH (non-condensing) Surge Protection 2KV Ingress Protection IP67

Reset Button N/A