



8MP ColorHunter Fixed Warm Light Turret Network Camera

IPC3638SE-ADF28K-WL-I0

SKU: 129233

Uniview IPC3638SE-ADF28K-WL-I0 8MP ColorHunter Fixed Warm Light Turret Network Camera

Features

- High quality image with 8MP, 1/1.8"CMOS sensor
- 8MP (3840*2160)@ 30(Intelligent off)/25fps; 5.3MP (3072*1728)@ 30/25fps; 3.6MP (2560*1440) @30/25fps; 2MP (1920*1080) @30/25fps; 720P (1280*720), Max 30/25fps
- Ultra 265, H.265, H.264, MJPEG
- Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
- Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
- Intelligent People Flow Counting and Crowd Density Monitoring
- Colorhunter technology ensures 24-hour full-color images
- F1.0 Super aperture
- 120dB true WDR technology enables clear image in strong light scene
- Support 9:16 corridor Mode
- Alarm:1 in/1 out, Audio: 1 in/1 out
- Supports 512 G micro SD card
- IK10 vandal resistant and IP67 protection

IPC3638SE-ADF28K-WL-I0 IPC3638SE-ADF40K-WL-I0 Camera Sensor 1/1.8"8.0 megapixel, progressive scan, CMOS Minimum Illumination Colour: 0.0005 lux (F1.0, AGC ON) Shutter Auto/Manual, 1 ~ 1/100000s Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 72° Rotate: 0° ~ 360° WDR 120dB S/N >56dB Lens Lens 2.8mm@F1.0 4.0mm@F1.0 Iris Fixed Field of View (H) 110.15° 94.29° Field of View (V) 59.06° 49.73° Field of View (D) 143.19° 115.97° DORI DORI Distance Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 63.0 25.2 12.6 6.3 4.0 90.0 36.0 18.0 9.0 Illuminator LED Distance Up to 30m (98ft) LEDs Number 2 LED On/Off Control Auto/Manual Video Video Compression Ultra265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main profile, High profile Frame Rate Main Stream: 8MP (3840*2160), Max 30fps;5.3MP (3072*1728), Max 30fps; 3.6MP (2560*1440), Max 30fps; 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; Third Stream: D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; Video Bit Rate 128 Kbps~16 Mbps U-code Support OSD Up to 8 OSDs Privacy Mask Up to 4 areas ROI Up to 8 areas Video Stream Triple streams Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital Noise Reduction 2D/3D DNR Smart Illumination Support Flip Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise Dewarping N/A HLC Support BLC Support Defog Digital Defog Intelligent Smart intrusion prevention Support false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection Statistical Analysis People counting, support people flow counting and crowd density monitoring Events Basic Detection Motion detection, Ultra motion detection, Tampering alarm, Audio Detection General Function Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication Audio Audio Compression G.711 Audio Bitrate 64 Kbps Two-way audio Support Suppression Support Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256 GB Network Storage ANR, NAS(NFS) Network Protocols IPv4, IPv6,IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS, SSH Compatible Integration ONVIF (Profile S, Profile G, Profile T), API,SDK User/Host Up to 32 users. 2 user levels: administrator and common user Security Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2,

WSSE and digest authentication for ONVIF Client EZStation EZView EZLive Web Browser Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above Interface Audio I/O Input: impedance 35k Ω ; amplitude 2V [p-p] Output: impedance 600 Ω ; amplitude 2V [p-p] Alarm I/O 1/1 RS485 N/A Built-in Mic Support Built-in Speaker N/A WIFI N/A Network 1 * RJ45 10M/100M Base-TX Ethernet Video Output N/A Certifications EMC CE-EMC (EN 55032: 2015+A1:2020, EN 61000-3-3: 2013+A1: 2019, EN IEC 61000-3-2: 2019+A1: 2021, EN 55035: 2017+A11:2020) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014) Safety CE LVD (EN 62368-1:2014+A11:2017) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01) Environment CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006) Protection IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013) IK10 (IEC 62262:2002) General Power DC 12V \pm 25%, PoE (IEEE 802.3af) Power consumption: Max 11W Power Interface Φ 5.5mm coaxial power plug Dimensions (Φ x H) 129 x 110mm (5.1" x 4.3") Weight 0.64kg (1.41lb) Material Metal Operating Conditions -30 $^{\circ}$ C ~ 60 $^{\circ}$ C (-22 $^{\circ}$ F ~ 140 $^{\circ}$ F), Humidity: \leq 95% RH (non-condensing) Storage Environment -30 $^{\circ}$ C ~ 60 $^{\circ}$ C (-22 $^{\circ}$ F ~ 140 $^{\circ}$ F), Humidity: \leq 95% RH (non-condensing) Surge Protection 4KV Reset Button Support