



## 8MP LightHunter Bullet IP Camera

IPC2328SB-DZK-I0

SKU: 61656    UPC: 810093000000

Monitor an indoor or outdoor area with the IPC2328SB-DZK-I0 8MP Network Bullet Camera from Uniview. This unit uses a 1/3" progressive scan CMOS sensor to capture 3840\*2160 resolution video at 20 fps. IR LEDs provide up to 98' of night vision. A built-in microphone enables this camera to pick up audio. A memory card slot supports microSD cards up to 256GB (available separately). Integrated PoE technology simplifies connectivity by enabling the transfer of power and data through a single cable.

This camera complies with ONVIF profiles G, S, and T, making it compatible with a wide range of surveillance devices. It is housed in an IP67-rated enclosure that is suitable for safe outdoor use.

### Features

High quality image with 8MP, 1/2.8" CMOS sensor

8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps; 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080)@30/25fps

Ultra 265, H.265, H.264, MJPEG

LightHunter technology ensures ultra-high image quality in low illumination environment

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Alarm: 1 in/1 out, Audio: 1 in/1 out

Smart IR, up to 50m (164ft) IR distance

Supports 256 G Micro SD card

IK10 vandal resistant

IP67 protection

Support PoE power supply

Camera Sensor 1/2.8" 8.0 megapixel, progressive scan, CMOS Lens 2.8 ~ 12mm, AF automatic focusing and motorized zoom lens DORI Distance - Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 86.9 34.8 17.4 8.7; 12 372.4 149.0 74.5 37.2 Angle of View (H) 107.4° ~ 29.2° Angle of View (V) 54.2° ~ 16.3° Angle of View (O) 111.0° ~ 33.1° Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 90° Rotate: 0° ~ 360° Shutter Auto/Manual, 1 ~ 1/1000000s Minimum Illumination Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on Day/Night IR-cut filter with auto switch (ICR) Digital Noise Reduction 2D/3D DNR S/N >56 dB IR Range Up to 50m (164ft) IR range Wavelength 850nm IR On/Off Control Auto/Manual Defog Digital Defog WDR 120dB Video Video Compression Ultra 265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main profile, High profile Frame Rate: Main Stream: 8MP (3840\*2160), Max 20fps; 5MP (3072\*1728), Max 30fps; 4MP (2560\*1440), Max 30fps; 1080P (1920\*1080), Max 30fps; Sub Stream: 1080P (1920\*1080), Max 30fps; 720P (1280\*720), Max 30fps; D1 (720\*576), Max 30fps; 640\*360, Max 30fps; 2CIF (704\*288), Max 30fps; CIF (352\*288), Max 30fps; Third Stream: D1 (720\*576), Max 30fps; 640\*360, Max 30fps; 2CIF (704\*288), Max 30fps; CIF (352\*288), Max 30fps; Video Bit Rate 128 Kbps ~ 16 Mbps OSD Up to 8 OSDs Privacy Mask Up to 4 areas ROI Up to 8 areas Motion Detection Up to 4 areas Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Smart IR Support Flip Normal/Vertical/Horizontal/180°/90° Clockwise/90° Anti-clockwise Dewarping Supported HLC Supported BLC Supported Audio Audio Compression G.711 Two-way audio Supported Suppression Supported Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256GB Network Storage ANR Network Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS Compatible Integration ONVIF (Profile S, Profile G, Profile T), API Client EZStation, EZView, EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below,



Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Interface Audio I/O - Input: impedance 35k $\Omega$ ; amplitude 2V [p-p]; Output: impedance 600 $\Omega$ ; amplitude 2V [p-p] Alarm I/O 1/1 Network 1 RJ45 10M/100M Base-TX Ethernet Certifications Certifications CE: EN 60950-1; UL: UL60950-1; FCC: FCC Part 15 General Power DC 12V $\pm$ 25%, PoE (IEEE 802.3af) Power consumption: Max 10.5W Dimensions (L x W x H) 245 x 86 x 72mm (9.6" x 3.4" x 2.8") Net Weight 0.92kg (2.03lb) Material Metal Working Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity:  $\leq$ 95% RH (non-condensing) Storage Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity:  $\leq$ 95% RH (non-condensing) Surge Protection 6KV Ingress Protection IP67 Vandal Resistant IK10 Reset Button N/A