



8MP Bullet IP Camera

IPC2128SB-ADF28KMC-IO

SKU: 61654 UPC: 810093000000

The IPC2128SB-ADF28KMC-IO Uniview 4K Active Deterrence IP Bullet Camera is an IO Series Bullet Style Camera with Light and Sound Alarms. It is also NDA Compliant so you can use it for applications that require NDA Guidelines. Lighthunter Technology provides extremely detailed color images even in low light. In addition, the camera has a built in PoE, and a built in MicroSD Card Slot for on board recording. With On Board Recording you will have a redundancy for your important data. With an extreme temperature range of -22°F to +140°F, this IP Camera can handle a variety of harsh environments. Weatherproof ratings on this professional grade camera are IP67 so you have maximum protection against the elements. Uniview Cameras have a wide voltage range and are capable of Long Range PoE runs of up to 300 Meters (980 Feet) when used with a Uniview NVR. Therefore, additional equipment is not required for long cable runs.

The IPC2128SB-ADF28KMC-IO has a 2.8mm Lens which has an AOV of 112.4° for a wide coverage area. In addition, you get a Built In Microphone and a Built In Speaker for 2 way communication. Prime IO Series Cameras are capable of smart functions such as Line Crossing, Intrusion Detection, and leaving or entering an area detection.

Features

- High-quality image with 8MP, 1/2.7" CMOS sensor
- 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080)@30/25fps
- Ultra 265, H.265, H.264, MJPEG
- 120dB true WDR technology enables clear image in the strong light scene
- Support 9:16 Corridor Mode
- Built-in Mic
- Built-in Speaker
- Smart IR, up to 30m (98ft) IR distance
- Supports 256 G Micro SD card
- IP67 protection
- Support PoE power supply

Camera Sensor 1/2.7" 8.0 megapixel, progressive scan, CMOS Lens 2.8mm@F2.0 4.0mm@F2.0 DORI Distance Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 84.0 33.6 16.8 8.4, 4.0 120.0 48.0 24.0 12.0 Angle of View (H) 112.4° 86.5° Angle of View (V) 60.1° 44.1° Angle of View (O) 146.1° 112.5° Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 90° Rotate: 0° ~ 360° Shutter Auto/Manual, 1 ~ 1/100000s Minimum Illumination Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on Digital noise reduction 2D/3D DNR Day/Night IR-cut filter with auto switch (ICR) S/N >56dB IR Range Up to 30m (98 ft) IR range Wavelength 850nm IR On/Off Control Auto/Manual Defog Digital Defog WDR 120dB Video Compression Ultra 265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main profile, High profile Frame Rate Main Stream: 8MP (3840*2160), Max 20fps; 5MP (3072*1728), Max 30fps; 4MP (2560*1440), Max 30fps; 1080P (1920*1080), Max 30fps; Sub Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; Third Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; Video Bit Rate 128 Kbps~16 Mbps OSD Up to 8 OSDs Privacy Mask Up to 4 areas ROI Up to 8 areas Motion Detection Up to 4 areas Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital Noise Reduction 2D/3D DNR Smart IR Support Flip Normal/Vertical/Horizontal/180°/90° Clockwise/90° Anti-clockwise Dewarping Supported HLC Supported



BLC Supported Audio Audio Compression G.711 Two-way audio Supported Suppression Supported Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256GB Network Storage ANR Network Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS Compatible Integration ONVIF (Profile S, Profile G, Profile T), API Client EZStation, EZView, EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Interface Network 1 RJ45 10M/100M Base-TX Ethernet Built-in Mic Supported Built-in Speaker Supported Alarm Light Supported Certifications Certifications CE: EN 60950-1; UL: UL60950-1; FCC: FCC Part 15 General Power DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 10.5W Dimensions (L x W x H) 191x 75 x 74mm (7.5" x 3.0" x 2.9") Net Weight 0.41kg (0.90lb) Material Metal Working Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 5%~95% RH (non-condensing) Storage Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 5%~95% RH (non-condensing) Surge Protection 2KV Ingress Protection IP67 Reset Button Supported