



4MP LightHunter Bullet IP Security Camera

IPC2124SR5-ADF28KM-G

SKU: 62722 UPC: 810093000000

Monitor an indoor or outdoor area with the IPC2124SR5-ADF28KM-G 4MP Network Bullet Camera from Uniview. This unit uses a 1/3" progressive scan CMOS sensor to capture 2688 x 1520 resolution video at 30 fps. IR LEDs provide up to 98€² of night vision. The camera's 2.8mm fixed lens delivers a 107.8° horizontal field of view. A built-in microphone enables this camera to pick up audio. A memory card slot supports microSD cards up to 256GB (available separately). Integrated PoE technology simplifies connectivity by enabling the transfer of power and data through a single cable.

This camera complies with ONVIF profiles G, S, and T, making it compatible with a wide range of surveillance devices. It is housed in an IP67-rated enclosure that is suitable for safe outdoor use.

Features

- 2688 x 1520 Resolution at 30 fps
- IR LEDs for Night Vision up to 98€²
- 2.8mm Fixed Lens
- 107.8° Horizontal Field of View
- Built-In Microphone
- Supports microSD Cards up to 256GB
- RJ45 Ethernet with PoE Technology
- Complies with ONVIF Profiles G, S & T
- IP67 Rated for Outdoor Use

Camera Sensor 1/3"4.0 megapixel, progressive scan, CMOS Lens 2.8mm@F2.0 4.0mm@F2.0 DORI Distance - Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 63.0 25.2 12.6 6.3 4.0 90.0 36.0 18.0 9.0 Angle of View (H) 107.8° 82.0° Angle of View (V) 57.0° 41.6° Angle of View (O) 140.1° 100.9° Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 90° Rotate: 0° ~ 360° Shutter Auto/Manual, 1 ~ 1/100000s Minimum Illumination Colour:0.01Lux (F2.0, AGC ON) 0Lux with IR on Digital noise reduction 2D/3D DNR Day/Night IR-cut filter with auto switch (ICR) S/N >56dB IR Range Up to 30m (98 ft) IR range Wavelength 850nm IR On/Off Control Auto/Manual Defog Digital Defog WDR 120dB Video Video Compression Ultra 265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main Profile Frame Rate : Main Stream: 4MP (2688*1520), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps;1080P(1920*1080),Max30fps; Sub Stream: 4CIF (704*576), Max 30fps;; Third Stream: CIF (352*288), Max 30fps Video Bit Rate 128 Kbps~16 Mbps OSD Up to 4 OSDs Privacy Mask Up to 4 areas ROI Up to 2 areas Motion Detection Up to 4 areas Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital noise reduction 2D/3D DNR Smart IR Support Flip Normal/Vertical/Horizontal/180° Dewarping NA HLC Supported BLC Supported Audio Compression G.711 Suppression Supported Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256GB Network Storage ANR Network Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL Compatible Integration ONVIF (Profile S, Profile G, Profile T), API Client EZStation, EZView, EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below; Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Interface Network 1 RJ45 10M/100M Base-TX Ethernet Built-in Mic Supported Certifications Certifications: CE: EN 60950-1, UL: UL60950-1, FCC: FCC Part 15 General Power DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 6.4W Dimensions (L x W x H) 165 x 63.1 x 62.5mm (6.5" x 2.5" x 2.5") Net Weight 0.45kg (0.99lb) Material Metal Working Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 0%~95% RH (non-condensing) Storage Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 0%~95% RH (non-condensing) Surge Protection 2KV Ingress Protection IP67