



4MP WDR IP IR Dome Camera

IPC3534SR3-DVPZ-F

SKU: 61622 UPC: 0235C3QV

Vandal Proof Dome (VPD) Networking / Internet Protocol Security Camera (IPC), 4MP@30FPS, 2.8-12mm Motorized, 1/3" CMOS, IR(98ft), DWDR, Surveillance Storage: Micro SD Card, also known as a TF (Trans Flash) Card, is a small flash memory card used in security cameras. (SD). UL Listed professional surveillance products. Remote viewing from your mobile with ENS Security. you can quickly and easily view your security system remotely through your smartphone, tablet, or PC.

Features

- Day/night functionality
- Smart IR, up to 30m (98ft) IR distance
- Up to 120 dB WDR (Wide Dynamic Range)
- 2D/3D DNR (Digital Noise Reduction)
- IR anti-reflection window to increase the infrared transmittance
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- Customized OSD
- Triple Stream
- ONVIF Conformance
- Built-in Mic
- Micro SD, up to 256GB
- Wide temperature range: -35°C ~ 60°C (-31°F ~ 140°F)
- Wide input voltage range of ±25%
- 3-Axis
- IP67
- IK10 vandal resistant

Camera Sensor 1/3"4.0 megapixel, progressive scan, CMOS Lens 2.8 ~ 12mm, AF automatic focusing and motorized zoom lens DORI Distance Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 63.0 25.2 12.6 6.3 12 270.0 108.0 54.0 27.0 Angle of view (H) 98.26°~ 31.35° Angle of View (V) 54.76°~ 18.55° Angle of View (O) 127.74°~36.99° Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 70° Rotate: 0° ~ 360° Shutter Auto/Manual, 1 ~ 1/100000s Minimum Illumination Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR Day/Night IR-cut filter with auto switch (ICR) Digital noise reduction 2D/3D DNR S/N >56dB IR Range Up to 30m (98ft) IR range Wavelength 850nm IR On/Off Control Auto/Manual Defog Digital Defog WDR 120dB Video Video Compression Ultra 265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main Profile Frame Rate Main Stream: 4MP (2688*1520), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps;1080P(1920*1080),Max30fps, Sub Stream: 4CIF (704*576), Max 30fps; Third Stream: CIF (352*288), Max 30fps Video Bit Rate 128 Kbps~16 Mbps OSD Up to 4 OSDs Privacy Mask Up to 4 areas ROI Up to 2 areas Motion Detection Up to 4 areas Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital noise reduction 2D/3D DNR Smart IR Support Flip Normal/Vertical/Horizontal/180° Dewarping NA HLC Supported BLC Supported Audio Audio Compression G.711 Suppression Supported Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256GB Network Storage ANR Network Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL Compatible Integration ONVIF (Profile S, Profile G, Profile T), API Client EZStation, EZView, EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below, Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Interface Audio I/O Input: impedance 35kΩ; amplitude 2V [p-p], Output: impedance 600Ω; amplitude 2V [p-p] Alarm I/O 1/1 Network 10M/100M Base-TX Ethernet Certifications



Certifications CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15 General Power DC 12V±25%, PoE (IEEE 802.3af)
Power consumption: Max 8.7W Dimensions (W x H) 128.1mmx99.9mm (5.04" x 3.93") Net Weight 0.57kg (1.26lb)
Material Metal + Plastic Working Environment -35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment -35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing) Surge Protection 6KV
Ingress Protection IP67 Vandal Resistant IK10 Reset Button Supported