



5MP HD ColorHunter Bullet IP Camera

IPC2225SE-DF40K-WL-I0

SKU: 61639 UPC: 810093000000

Monitor an indoor or outdoor area with the IPC2225SE-DF40K-WL-I0 5MP Network Bullet Camera from Uniview. This unit uses a 1/3" progressive scan CMOS sensor to capture 2880*1620 resolution video at 25 fps. IR LEDs provide up to 164' of night vision. Two-way audio is possible thanks to an audio input and output. A memory card slot supports microSD cards up to 256GB (available separately). Integrated PoE technology simplifies connectivity by enabling the transfer of power and data through a single cable.

This camera complies with ONVIF profiles G, S, and T, making it compatible with a wide range of surveillance devices. It is housed in an IP67-rated metal enclosure that is suitable for outdoor use.

Features

- High quality image with 5MP, 1/2.7" CMOS sensor
- 5MP (2880*1620)@25fps; 4MP (2560*1440)@25fps; 3MP (2304*1296)@25fps; 2MP (1920*1080)@30/25fps;;
- Ultra 265, H.265, H.264, MJPEG
- Colorhunter technology ensures 24-hour full-color images
- 120dB true WDR technology enables clear image in strong light scene
- Support 9:16 corridor Mode
- Alarm: 1 in/1 out, Audio: 1 in/1 out
- Supports 256 G micro SD card
- IK10 vandal resistant
- IP67 protection
- Support PoE power supply

Camera Sensor 1/2.7", 5.0 megapixel, progressive scan, CMOS Lens 4.0mm@F1.0 6.0mm@F1.0 DORI Distance Lens (mm) Detect 1/4" ~ 1/4" Observe 1/4" ~ 1/4" Recognize 1/4" ~ 1/4" Identify 1/4" ~ 1/4" 4.0 90.0 36.0 18.0 9.0 6.0 135.0 54.0 27.0 13.5 Angle of View (H) 80.2° 53.4° Angle of View (V) 43.0° 29.2° Angle of View (O) 94.7° 61.6° Adjustment angle Pan: 0°~ 360° Tilt: 0°~ 90° Rotate: 0°~ 360° Shutter Auto/Manual, 1 ~ 1/100000s Minimum Illumination Colour: 0.001Lux (F1.0, AGC ON) S/N >56dB Defog Digital Defog WDR 120dB LEDs Number 2 LED Distance Up to 30m (98ft) Video Video Compression Ultra265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main profile, High profile Frame Rate ; Main Stream: 5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 25fps; 2MP (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF (704*288), Max 30fps; CIF (352*288), Max 30fps; Third Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF (704*288), Max 30fps; CIF (352*288), Max 30fps; Video Bit Rate 128 Kbps~16 Mbps 9:16 Corridor Mode Supported OSD Up to 8 OSDs Privacy Mask Up to 4 areas ROI Up to 8 areas Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital noise reduction 2D/3D DNR Smart Illumination Support Flip Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise Dewarping Support HLC Support BLC Support Audio Audio Compression G.711 Two-way audio Supported Suppression Supported Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256GB Network Storage ANR, NAS(NFS) Network Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS Compatible Integration ONVIF (Profile S, Profile G, Profile T), API Client EZStation, EZView, EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below, Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Interface Audio I/O Input: impedance 35kΩ; amplitude 2V [p-p]; Output: impedance 600Ω; amplitude 2V [p-p] Alarm I/O 1/1 Network 1 RJ45 10M/100M Base-TX Ethernet Certifications Certifications CE: EN 60950-1; UL: UL60950-1; FCC: FCC Part 15 General Power DC 12V±25%, PoE (IEEE 802.3af) Power consumption:



Max 9.0W Dimensions (L x W x H) 246x 86 x 85mm (9.7" x 3.4" x 3.3") Net Weight 0.92kg (2.02lb) Material Metal
Working Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) Storage Environment -
30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) Surge protection 4KV Ingress Protection IP67
Vandal Resistant IK10 Reset Button N/A