



## 4MP HD IR VF Eyeball Network Camera

IPC3634SR3-ADZK-G-BK

SKU: 65874

The IPC3634SR3-ADZK-G-BK Uniview 4MP IP Turret Dome Camera is a Prime Series Dome with Motorized Zoom and Perimeter Detection. It is also NDAA Compliant so it can be used in applications that require NDAA Compliance. These 4MP IP Cameras now feature Intrusion Detection Technology, and up to 131 Feet of Night Vision. In addition, the camera has a built in PoE, and a built in MicroSD Card Slot for on board recording.

With an extreme temperature range of -22°F to +140°F, you can rest assured that this IP Camera can handle a variety of harsh environments. Weatherproof ratings on this professional grade camera are IP67 which gives you maximum protection against the elements. Uniview Cameras have a wide voltage range and are capable of Long Range PoE runs of up to 300 Meters (980 Feet) when used with a Uniview NVR. Therefore, additional equipment is not required for your long cable runs.

The IPC3634SR3-ADZK-G-BK Uniview 4MP IP Dome Camera has a 2.8-12mm Motorized Zoom Lens with Auto Focus. This Prime Series UNV Dome also has a Built In Microphone so you can record Audio to your NVR.

### Features

:

High-quality image with 4MP, 1/3" CMOS sensor

4MP (2688\*1520)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296)@ 30/25fps; 2MP (1920\*1080)@30/25fps

Ultra 265, H.265, H.264, MJPEG

120dB true WDR technology enables clear image in the strong light scene

Support 9:16 Corridor Mode

Built-in Mic

Smart IR, up to 40m (131ft) IR distance

Supports 256 G Micro SD card

IP67 protection

Support PoE power supply

3-Axis

Camera Sensor 1/3"4.0 megapixel, progressive scan, CMOS Lens 2.8 ~ 12mm, AF automatic focusing and motorized zoom lens DORI Distance Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 42 16.8 8.4 4.2 12 180 72 36 18 Angle of View (H) 102.79°~ 30.86° Angle of View (V) 54.50°~ 17.49° Angle of View (O) 106.94°~35.49° Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 75° Rotate: 0°~ 360° Shutter Auto/Manual, 1 ~ 1/100000s Minimum Illumination Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR Day/Night IR-cut filter with auto switch (ICR) Digital Noise Reduction 2D/3D DNR S/N >56dB IR Range Up to 40m (131ft) IR range Wavelength 850nm IR On/Off Control Auto/Manual Defog Digital Defog WDR 120dB Video Video Compression Ultra 265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main profile, High profile Frame Rate Main Stream: 4MP (2688\*1520), Max 30fps; 4MP (2560\*1440), Max 30fps; 3MP (2304\*1296), Max 30fps; 1080P (1920\*1080), Max 30fps; Sub Stream: 720P (1280\*720), Max 30fps; D1 (720\*576), Max 30fps; 640\*360,Max 30fps; 2CIF(704\*288), Max 30fps; CIF(352\*288), Max 30fps; Video Bit Rate 128 Kbps~16 Mbps 9:16 Corridor Mode Supported OSD Up to 4 OSDs Privacy Mask Up to 4 areas ROI Up to 8 areas Motion Detection Up to 4 areas Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital Noise Reduction 2D/3D DNR Smart IR Supported Flip Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-

clockwise Dewarping N/A HLC Supported BLC Supported Audio Audio Compression G.711 Suppression Supported  
Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256GB Network Storage ANR, NAS(NFS) Network  
Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP,  
HTTPS, SMTP, SSL, QoS, 802.1x, SNMP Compatible Integration ONVIF (Profile S, Profile G, Profile T), API Client  
EZStation, EZView, EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below,  
Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Interface Network 10M/100M Base-TX  
Ethernet Built-in Mic Supported Certifications Certifications CE: EN 60950-1, UL: UL60950-1, FCC: FCC Part 15  
General Power DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 8.0W Dimensions (W x H): 129 x 110mm  
(5.1" x 4.3") Net Weight 0.67kg (1.48lb) Material Metal Working Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity:  
±95% RH (non-condensing) Storage Environment -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ±95% RH (non-  
condensing) Surge Protection 6KV Ingress Protection IP67 Reset Button Supported