



## 4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera

IPC3614SB-ADF28KMC-I0

SKU: 62730    UPC: 810093000000

Uniview 4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera ipc3614sb-adf28kmc-i0

### Features

High quality image with 4MP, 1/2.7"CMOS sensor

4MP (2688\*1520)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;

Ultra 265, H.265, H.264, MJPEG

Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection

Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle

Supports sound and light alarm linkage. When Smart intrusion prevention is triggered, the camera links sound alarm and light linkage.

Intelligent People Flow Counting and Crowd Density Monitoring

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Built-in Mic and Speaker

Smart IR, up to 30m (98ft) IR distance

Supports 256 G Micro SD card

IP67 protection

Support PoE power supply

Specifications IPC3614SB-ADF28KMC-I0 IPC3614SB-ADF40KMC-I0 Camera Sensor 1/2.7"4.0 megapixel, progressive scan, CMOS Minimum Illumination Colour: 0.002 lux (F1.6, AGC ON) 0 lux with IR on Day/Night IR-cut filter with auto switch (ICR) Shutter Auto/Manual, 1 ~ 1/100000s Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 80° Rotate: 0° ~ 360° WDR 120dB S/N >56dB Lens Lens type 2.8mm@F1.6 4.0mm@F1.6 Iris Fixed Field of View (H) 101.1° 83.7° Field of View (V) 55.3° 44.9° Field of View (D) 111.1° 89.2° DORI DORI Distance Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m) 2.8 63.0 25.2 12.6 6.3 4.0 90.0 36.0 18.0 9.0 Illuminator Illumination Distance(IR) Up to 30m (98 ft) Illumination Distance(Warm Light) Up to 30m (98 ft) Wavelength 850nm IR On/Off Control Auto/Manual Video Video Compression Ultra 265, H.265, H.264, MJPEG H.264 code profile Baseline profile, Main profile, High profile Frame Rate Main Stream: 4MP (2688\*1520), Max 30fps; 4MP (2560\*1440), Max 30fps; 3MP (2304\*1296), Max 30fps; 1080P (1920\*1080), Max 30fps; Sub Stream: 720P (1280\*720), Max 30fps; D1 (720\*576), Max 30fps; 640\*360, Max 30fps; Third Stream: D1 (720\*576), Max 30fps; 640\*360, Max 30fps; 2CIF(704\*288), Max 30fps; CIF(352\*288), Max 30fps; Video Bit Rate 128 Kbps~16 Mbps U-code Support OSD Up to 8 OSDs Privacy Mask Up to 4 areas ROI Up to 8 areas Video Stream Triple streams Image White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 Digital Noise Reduction 2D/3D DNR Smart IR Support Flip Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise Dewarping N/A HLC Supported BLC Supported Defog Digital Defog Intelligent Smart intrusion prevention Support false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection Statistical Analysis People counting, support people flow counting and crowd density monitoring Events Basic Detection Motion detection, tampering alarm, audio detection General Function Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication Audio Audio Compression G.711 Audio Bitrate 64 Kbps Two-way audio Supported Suppression Supported Sampling Rate 8KHZ Storage Edge Storage Micro SD, up to 256 GB Network Storage ANR, NAS(NFS) Network Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH Compatible

Integration ONVIF (Profile S, Profile G, Profile T), API, SDK User/Host Up to 32 users. 2 user levels: administrator and common user Security Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF Client EZStation EZView EZLive Web Browser Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+ Interface Audio I/O N/A Alarm I/O N/A RS485 N/A Built-in Mic Support Built-in Speaker Support WIFI N/A Network 1 \* RJ45 10M/100M Base-TX Ethernet Video Output N/A Certifications EMC CE-EMC (EN 55032: 2015+A1:2020, EN 61000-3-3: 2013+A1: 2019, EN IEC 61000-3-2: 2019+A1: 2021, EN 55035: 2017+A11:2020) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014) Safety CE LVD (EN 62368-1:2014+A11:2017) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01) Environment CE-RoHS (2011/65/EU; (EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006) Protection IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013) General Power DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 7.5W Power Interface 5.5mm coaxial power plug Dimensions (W x H) 111 x 95mm (4.4" x 3.7") Weight 0.44kg (0.970lb) Material Metal + Plastic Working Environment -30°C ~ 55°C (-22°F ~ 131°F), Humidity: ≤95% RH (non-condensing) Storage Environment -30°C ~ 55°C (-22°F ~ 131°F), Humidity: ≤95% RH (non-condensing) Surge Protection 4KV Reset Button N/A