



8" 2-Way Dual Tweeter Stereo Input Rock Speaker - Sandstone

SC-RS8Si-SANDSTONE

SKU: 66905

8" two-way, dual tweeter stereo input rock loudspeaker, with living-room-quality sound outdoors. Can be used in mono, two-speaker stereo, or single-speaker stereo input. No-fade protective paint and weatherproof design that surpasses military standard 883 for corrosion resistance.

Features

- 8" TCC Polypropylene Dual Voice Coil Woofer
- Dual 1" Fluid-cooled Tri-laminate Teteron Tweeter
- Low Diffraction MicroPerf Aluminum Grilles
- Dual Precision Crossovers
- Multi-layer Fiberglass Construction
- Dimensions (L x D x H) 19.5" x 16.5" x 12.5" 495.3 x 419.1 x 317.5 mm
- Weight: 16.5 lbs. (7.5 kg)

Specifications
Tweeter: Dual 1" Teteron Tweeters
Woofer: 8" DVC TCC Polypropylene Woofer
Recommended Amplifier Power: 10-200 Watts
Frequency Response (+/- 3dB): 50 Hz - 21 kHz
Impedance: 8 Ohm Stereo / L/R Summed (parallel) 4 Ohm
Sensitivity (for 2.83V of Pink Noise): 89 dB
Temperature Extremes: - 50° to 185° F (-45° to 85° C)
Dimensions (L x D x H): 19.5" x 16.5" x 12.5" / 495.3 x 419.1 x 317.5 mm
Weight: 16.5 lbs. (7.5 kg)
General Family RS PRO Rocks
Frequency Response 50Hz - 21kHz +/-3dB
Impedance 8 (Ohms)
Power Handling 200 (Watts)
Sensitivity 88 (dB)
Dimensions 12-1/2" high x 19-1/2" wide x 16-1/2" deep
Other Specifications
Impedance 8 ohms in two-speaker stereo mode; 4 ohms in single-speaker stereo input "æSi" mode
Recommended amplifier power 10W to 200W
Sensitivity 88dB for 2.83V pink noise