



12-Channel 30W Multi-Zone Amplifier

SC12-30

SKU: 66912

The SC12-30 is a 12-channel, fully configurable power amplifier that provides 30W per channel (80W when bridged) and our unique BusMatrix Selector. The SC12-30 is the perfect multi-zone or multi-room solution.

Offering the classic SpeakerCraft stability that you™ve come to know and trust, the powerful SC12-30 will exceed your installation needs. Specifically designed to solve the problems of interfacing with different brands and models of equipment, and different rooms and applications, the SC12-30 makes installation easier and more straight forward than ever before. Fully configurable, with 12-channels that provide 30W per channel (80W when bridged) and our unique BusMatrix Selector, the SC12-30 is the perfect multi-zone or multi-room solution.

Features

- Delivers real world power at a solid 30W per channel RMS into 8 Ω and 40W per channel RMS into 4 Ω .
- Features three turn-on modes: Manual Turn-on via the Front Panel Switch, Audio Sense and External Voltage Trigger.
- Twelve to six-channel configurable power via the bridging switches located between each output pairs.
- Unique BusMatrix Selector enables flexibility to assign each channel to a common or dedicated signal input.
- Ensures extremely high channel-to-channel isolation, enabling freedom from noise and crosstalk.
- Dimensions (L x W x H) 16.25 x 17.25 x 5.75 in

Specifications 30 watts RMS per channel into 8 Ohms (all channels driven) 40 watts RMS per channel into 4 Ohms (all channels driven) Adjacent channels are bridgable to 80 watts RMS into 8 Ohms (all channels driven) Voltage trigger input accepts 3-24VAC/DC 12-volt control out Removable line cord Rack mount ears included Two-year limited warranty General Number of Channels12 Watts RMS Per Channel30 Rack MountableYes Rack Ears IncludedYes Dimensions17.25" (43.81cm) wide 5.75" (14.47cm) high (including feet) 16.25" (41.11cm) deep Weight35 lb. (15.8 kg) Shipping Info Length23.1 (Inches) Width19.3 (Inches) Height10.1 (Inches) Weight40.05 (Lbs) Unit of Measure Each UPC664254999680 Master Pack Qty2 Other Specifications 30 watts RMS per channel into 8 Ohms (all channels driven) 40 watts RMS per channel into 4 Ohms (all channels driven) Adjacent channels are bridgable to 80 watts RMS into 8 Ohms (all channels driven) Voltage trigger input accepts 3-24VAC/DC 12-volt control out Removable line cord Rack mount ears included Two year limited warranty