



100 OD 6 6" Outdoor Speaker - White

FOAOPA1OD60W100

SKU: 62856 UPC: 3544050000000

In addition to its UV-treated, high-density Polypropylene damping cabinet, the 100 OD6* loudspeaker is IP66 certified** (Ingress Protection rating 66). This reference international standard demonstrates the remarkable resistance of products to extreme weather conditions, and more specifically their watertight and dust-proof qualities. Integrating Focal Technologies, the 100 OD6 loudspeaker delivers the Focal's high-fidelity sound outdoors. It is also easy to install, thanks to its reinforced, notched assembly bracket. Its 180-degree rotation system makes it easy to position, too. And because, at Focal, attention is paid to each and every detail and to satisfying every taste, the grille and cabinet are available in black finish or white ready-to-paint finish. Focal is a famous name in high-performance home and car audio, so we're glad to see them venture into the realm of outdoor speakers. The Focal 100 OD6 features a 6-1/2" woofer and an inverted aluminum dome tweeter in a UV-treated vibration-damping polypropylene cabinet. The woofer receives Focal's proprietary Polyglass treatment, which involves coating the cone with molten glass micro balls, for superior rigidity and accuracy. These speakers are sold single, so you can wire up as many as it takes to bring beautiful music to your pool, patio, or backyard.

Features

- 6-1/2" woofer with waterproof polypropylene cone and Polyglass treatment
- inverted aluminum dome tweeter
- frequency response 65-23,000 Hz (± 3 dB)
- sensitivity: 87 dB
- impedance: 8 ohms
- handles up to 120 watts RMS
- UV-treated high-density polypropylene cabinet
- IP66-rated waterproof and dustproof
- spring-loaded wire terminals with silicone weather seal
- paintable aluminum grille
- aluminum bracket with 180° articulation included
- rotating logo for horizontal or vertical installation

Enclosure Acoustic Suspension Tweeter Type Inverted Hard-Dome Midrange Size None Woofer Size 6-1/2 Woofer Composition Polyglass Woofer Surround Rubber Power Range (watts) 20-120 Sensitivity 87 dB Impedance (ohms) 8 Frequency Response 65-23k Hz Connector Type Spring post Height (inches) 12-9/16 Width (inches) 8-15/16 Depth (inches) 10-5/16 Weight (pounds) 9 Mounting Bracket Included Yes