



Gate io Gate Controller (Wireless)

GCW

SKU: 38885

PDK Gate Wireless IO NEMA Low Voltage Wall Mount GCW

The gate io comes in a sturdy, weatherproof enclosure, perfect for all outdoor openings exposed to the elements such as gates and garages. The gate io is perfect for gated entrances, and openings exposed to the elements or harsher environments. Never worry about costly trenching ever again. The gate io comes in a sturdy lockable NEMA 4X UL-rated weatherproof enclosure. Powerfully equipped with WiMAC wireless, the gate io can reach up to one-mile line of sight.

Features

- Gate io Controller-Wireless
- NEMA, Low Voltage, Wall Mount. (For Pole Mount add PM-05-PMK)
- Power Supply Input
- Industrial-grade 2A Form-C Relays (1 Door / 1 Aux)
- Power Supply: ELK-TRG1640 or HVC

Connections Removable Screw-down Terminals Power Supply Input Industrial-grade 2A Form-C Relays (1 Door / 1 Aux) Reader Input (2) Input A (Door Position Sensor) Input B (Request To Exit) Enclosure Dimensions (W x H x D) 7" x 9.25" x 2.25" Polycarbonate lockable security enclosure NEMA 4X UL-rated enclosure Weight GCE/GCPOE/GCW - 1.31 lbs (21 oz) Optional Parts Pole Mount Kit (PMK) Communication Options Ethernet PoE WiMACTM Wireless Mesh (2.4 GHz / 802.15.4) Encryption: AES 128bit Wireless Range: 1 Mile LoS, 450ft indoor average Environmental Temperature: -20Â° ~ +60Â° C or -4Â° ~ +140Â° F Humidity: 0 - 95% relative humidity non condensing Power 12-24V AC/DC Input 12VDC 1.5A *Battery-Backed Output Powers readers and other door hardware directly from the bus *Power supply and battery not included