



## Modular IP Camera with 2.8mm Pinhole Sensor

DS-2CD6425G1-20 2.8mm

SKU: 131417    UPC: 842571000000

Designed for covert surveillance, the Hikvision DS-2CD6425G1-20 2MP Modular Network Camera with 2.8mm Pinhole Sensor includes a main body and an L-shaped sensor unit with a 2.8mm pinhole lens and 6.6' cable for flexible placement. The camera uses a 1/2.8" progressive scan CMOS sensor to capture 1080p resolution video at 30 fps. A 93.9° horizontal field of view is delivered by the 2.8mm lens. Two-way audio is possible thanks to an audio input and output. A memory card slot supports microSD cards up to 256GB (available separately). Integrated PoE technology simplifies connectivity by enabling the transfer of power and data through a single cable.

### Features

- Designed for Covert Surveillance
- Main Body & Sensor Unit with 6.6' Cable
- 1920 x 1080 Resolution at 30 fps
- 2.8mm Fixed Pinhole Lens
- 93.9° Horizontal Field of View
- Two-Way Audio

Sensor	2 MP 1/2.8" CMOS
Focal Length	2.8mm
Maximum Aperture	f/2.5
Lens Field of View	Horizontal: 93.9° Vertical: 51.7° Diagonal: 109.3°
IR Cut Filter	Mechanical
Day/Night	Yes
Minimum Illumination	Color: 0.002 Lux
Shutter Speed	1/100000 to 1/3 Seconds
Streaming Resolution	1920 x 1080 at 30 fps
Supported Video Compression	H.264, H.265, MJPEG
Multi-View Streaming	Yes, 3 Streams
Automatic Gain Control	Yes
1- or 2-Way Audio	Two-Way
Power Source	DC, PoE 802.3af (15 W)