



**HIKVISION®**

## 20MP Outdoor 4-Sensor Network Dome Camera with Night Vision & Heater

DS-2CD6D54FWD-IZHS

SKU: 17227    UPC: 842571113624

The DS-2CD6D54FWD-IZHS from Hikvision is a multi-sensor camera that uses four 1/2.7" progressive scan CMOS sensors to capture video at a total resolution of 10240 x 1920. Each sensor captures 2560 x 1920 resolution video at 24 fps. IR LEDs provide up to 98' of night vision. The camera is equipped with four 2.8-12mm varifocal lenses. Two-way audio communication is possible thanks to an audio input and output. A built-in memory card slot accepts microSD/SDHC/SDXC cards up to 128GB (available separately). Integrated PoE technology simplifies connectivity by transferring power and data through a single cable.

This camera complies with ONVIF profiles S & G making it compatible with a wide range of surveillance devices. It is equipped with a built-in heater. The camera is housed in an IP67- and IK10-rated enclosure that is suitable for outdoor use in areas at risk of vandalism.

### Features:

- 101 to 30 degree horizontal field of view
- 4 x 3-axis gimbals for flexible adjustment
- Camera pivots horizontally from -180 to 180 degree & vertically from 0 to 135 degree
- 0 to 355 degree rotation range
- H.265+ H.265 H.264+ H.264 and MJPEG video compressions
- SVC (scalable video coding)
- 120 dB wide dynamic range
- Automatic gain control
- 3D-DNR
- Picture overlay
- Backlight compensation
- Electronic image stabilization
- ROI (region of interest) supports four fixed regions for each stream
- Image settings include rotate mode saturation brightness contrast sharpness and white balance
- General functions include one-key reset anti-flicker mirror heartbeat password protection privacy masking watermark and IP address filtering
- Analytics include motion line crossing intrusion region entrance region exiting unattended baggage object removal face detection scene change defocus and audio exception detection
- Environmental noise filtering
- Two alarm inputs and two alarm outputs
- Alarm triggers include motion detection video tampering alarm network disconnected IP address conflict illegal login HDD full and HDD error
- Simultaneous live views for up to twenty channels
- Up to thirty-two users at three host levels (admin operator and user)
- Reset button
- RS-485 interface
- Compatible with Internet Explorer 8 or higher Chrome 31-44 Firefox 30.0-51 iOS Android and iVMS-4200
- Network-attached storage support
- CSA FCC CE and cUL certified